



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





Extensive range of accessories for the FieldPower®

Cable seals, terminal rails, locking elements and much more.

General ordering data

Version	Field Power® terminal rail, Steel, galvanized, 80 mm, for aluminium lid
Order No.	<u>2633730000</u>
Туре	FP ENC DR07 080 XC A
GTIN (EAN)	4050118664379
Qty.	5 items





Weidmüller Interface GmbH & Co. KG

2

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

ROHS	Conform				
Dimensions and weights					
			, , , , , , , , , , , , , , , , , , ,		
Depth	7.5 mm	Depth (inches)	0.2953 inch		
Height	35 mm	Height (inches)	1.378 inch		
Width	80 mm	Width (inches)	3.1496 inch		
Net weight	26 g				
Temperatures			,		
torage temperature		Operating temperature	-40 °C85 °C		
Environmental Product Comp	liance		<u>'</u>		
RoHS Compliance Status	Compliant without exemption				
REACH SVHC	No SVHC above 0.1 wt%				
General specifications			,		
Installation advice	Screws included	Insulating material	Steel		
Basic material	Steel, galvanized	Colour	silver		
General data					
Basic material	Steel, galvanized	Insulating material	Steel		
Colour	silver	Type of mounting	Screw mounting		
Mounting position, installation notice	for aluminium lid	Installation advice	Screws included		
Version	with slot				
Classifications					
ETIM 6.0	EC001285	ETIM 7.0	EC001285		
ETIM 8.0	EC001285	ETIM 9.0	EC001285		
ETIM 10.0	EC001285	ECLASS 9.0	27-40-06-02		
ECLASS 9.1	27-40-06-02	ECLASS 10.0	27-40-06-02		
ECLASS 11.0	27-40-06-02	ECLASS 12.0	27-40-06-02		
ECLASS 13.0	27-40-06-02	ECLASS 14.0	27-40-06-02		
ECLASS 15.0	27-40-06-02				

Catalogue status / Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Bits E6,3 - Torx®



The Weidmüller bits are standard bits which are highly popular with users thanks to their good quality, large range and efficiency. The computer-controlled hardening method enables Weidmüller to guarantee a consistently high standard of quality.

The high-quality raw materials used make it possible to reach torques far higher than any of those specified in the relevant DIN standards:

- DIN 5261 for PH/PZ bits,
- DIN 5263 for slotted bits.
- · Camcar standard for TORX bits

That means a long life at high torques and hence ideal conditions for standard situations.

The benefits:

- Suitable for all types of screws. Because of their excellent hardness values of 59-61 HRC, they are suitable for use with both manual and power tools.
- Good wearing resistance and thus a long life expectancy.
- Optimum fit in all DIN screws means low wear and optimum torque transmission.
- Manufactured to meet professional quality criteria according to relevant ISO standards with a consistently high standard of quality.

General ordering data

Type BIT E6,3 T20 X 150
Order No. 2821510000
GTIN (EAN) 4064675359050
Oty. 5 ST

Version Mounting tool

DMS PRO



Weidmüller torque screwdrivers have an ergonomic design and are therefore ideal for use with one hand. They can be used without causing fatigue in all installation positions. Apart from that, they incorporate an automatic torque limiter and have a good reproducibility accuracy.

General ordering data

Type DMS PRO
Order No. 1479120000
GTIN (EAN) 4050118287011
Qty. 1 ST

Version Mounting tool

Creation date 27.11.2025 04:17:45 MEZ

Catalogue status / Drawings 4