

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





Extensive range of accessories for the FieldPower®

Cable seals, terminal rails, locking elements and much more.

General ordering data

Version	Field Power® terminal rail, Steel, galvanized, 110 mm, for aluminium lid		
Order No.	<u>2633750000</u>		
Туре	FP ENC DR07 110 3C A		
GTIN (EAN)	4050118664362		
Qty.	5 items		





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Conform		
Comom		
7.5 mm	Depth (inches)	0.2953 inch
35 mm		1.378 inch
110 mm		4.3307 inch
36 g		
	Operating temperature	-40 °C85 °C
liance		,
Compliant without exemption		
No SVHC above 0.1 wt%		
Scrowe included	Inculating material	Steel
Steel, galvanized	Colour	silver
Steel, galvanized	Insulating material	Steel
silver	Type of mounting	Screw mounting
	Installation advice	Screws included
with slot		
FC00120F	ETINA 7.0	FC00120F
		EC001285
		EC001285
		27-40-06-02
		27-40-06-02
		27-40-06-02
27-40-06-02	ECLASS 14.0	27-40-06-02
	35 mm 110 mm 36 g Compliant without exer No SVHC above 0.1 wt Screws included Steel, galvanized Steel, galvanized silver for aluminium lid with slot EC001285 EC001285 EC001285 27-40-06-02 27-40-06-02 27-40-06-02	7.5 mm Depth (inches) 35 mm Height (inches) 110 mm Width (inches) 36 g Operating temperature Compliant without exemption No SVHC above 0.1 wt% Screws included Insulating material Steel, galvanized Colour Steel, galvanized Insulating material Type of mounting Installation advice with slot EC001285 ETIM 7.0 EC001285 ETIM 9.0 EC001285 ECLASS 9.0 ECLASS 10.0 27-40-06-02 ECLASS 12.0 27-40-06-02 ECLASS 12.0 ECLASS 12.0 ECLASS 14.0

Catalogue status / Drawings 2





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Bits E6,3 - Torx®



The Weidmüller bits are standard bits which are highly popular with users thanks to their good quality, large range and efficiency. The computer-controlled hardening method enables Weidmüller to guarantee a consistently high standard of quality.

The high-quality raw materials used make it possible to reach torques far higher than any of those specified in the relevant DIN standards:

- DIN 5261 for PH/PZ bits,
- DIN 5263 for slotted bits.
- · Camcar standard for TORX bits

That means a long life at high torques and hence ideal conditions for standard situations.

The benefits:

- Suitable for all types of screws. Because of their excellent hardness values of 59-61 HRC, they are suitable for use with both manual and power tools.
- Good wearing resistance and thus a long life expectancy.
- Optimum fit in all DIN screws means low wear and optimum torque transmission.
- Manufactured to meet professional quality criteria according to relevant ISO standards with a consistently high standard of quality.

General ordering data

Type BIT E6,3 T20 X 150
Order No. 2821510000
GTIN (EAN) 4064675359050
Oty. 5 ST

Version Mounting tool

DMS PRO



Weidmüller torque screwdrivers have an ergonomic design and are therefore ideal for use with one hand. They can be used without causing fatigue in all installation positions. Apart from that, they incorporate an automatic torque limiter and have a good reproducibility accuracy.

General ordering data

 Type
 DMS PRO

 Order No.
 1479120000

 GTIN (EAN)
 4050118287011

Version Mounting tool

Qty. 1 ST

Creation date 28.11.2025 12:00:01 MEZ

Catalogue status / Drawings 4