

SAI-M12-KBC-26/28**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

The crimp connection is characterised by high functional reliability. With this connection technology, the conductor is crimped to the contact and then engaged in the contact carrier. The connection between the conductor and crimp is vibration-resistant and boasts long-term stability. Crimp contacts are to be ordered separately.

General ordering data

| Version | Contact |
|------------|----------------------------|
| Order No. | 2673740000 |
| Type | SAI-M12-KBC-26/28 |
| GTIN (EAN) | 4050118755084 |
| Qty. | 100 items |

SAI-M12-KBC-26/28

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Dimensions and weights

| | |
|------------|--------|
| Net weight | 0.26 g |
|------------|--------|

Environmental Product Compliance

| | |
|--------------------------------------|--------------------------------------|
| RoHS Compliance Status | Compliant with exemption |
| RoHS Exemption (if applicable/known) | 6c |
| REACH SVHC | Lead 7439-92-1 |
| SCIP | ebf89fc8-a87f-4691-b87a-dfb9921774b4 |

Technical data customisable plug-in connectors

| | | | |
|--------------------------------|----------------------|--------------------------------|----------------------|
| Contact surface | Gold-plated | Connection cross-section | AWG 26 - AWG 28 |
| Type of connection | Crimp connection | Contact material | Copper alloy |
| Nominal current | 7 A | Plugging cycles | ≥ 250 |
| Pollution severity | 3 | Gender of contact | Female |
| Connection cross-section, max. | 0.13 mm ² | Connection cross-section, min. | 0.08 mm ² |

General Info

| | | | |
|--|----------------------|--|----------------------|
| Connection 1 | M12 Contact | Connection 2 | Crimp |
| Contact material | Copper alloy | Contact surface | Gold-plated |
| Wire connection cross section, finely stranded, min. | 0.08 mm ² | Wire connection cross section, finely stranded, max. | 0.13 mm ² |
| Wire cross-section, solid, min. | 0.08 mm ² | Wire cross-section, solid, max. | 0.13 mm ² |
| Plugging cycles | ≥ 250 | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC000796 | ETIM 9.0 | EC000796 |
| ETIM 10.0 | EC000796 | ECLASS 14.0 | 27-44-02-92 |
| ECLASS 15.0 | 27-44-02-92 | | |

SAI-M12-KBC-26/28**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Accessories****...for M12**

Weidmüller offers a wide range of tools and accessories for sensor-actuator cabling.

General ordering data

| | | |
|------------|----------------------------|--------------------------------------|
| Type | SAI-TMCSK | Version |
| Order No. | 1381690000 | Pressing tool, 4-indent crimp |
| GTIN (EAN) | 4050118183870 | |
| Qty. | 1 ST | |
| Type | SAI-TMC-PD | Version |
| Order No. | 1381700000 | Crimping tool insert, 4-indent crimp |
| GTIN (EAN) | 4050118183856 | |
| Qty. | 1 ST | |