

TC INL THIRD 7



Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Inspired by 5S and lean management methods, Weidmüller foam inserts ensure an efficient and tidy workplace. Designed according to a modular principle, they offer many advantages and can be selected according to individual requirements.

General ordering data

Order No.	2683860000
Туре	TC INL THIRD 7
GTIN (EAN)	4050118701975
Qty.	1 items

Catalogue status / Drawings



TC INL THIRD 7



Weidmüller Interface GmbH & Co. KG

21-07-04-12

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Approvals			
ROHS	Conform		
Dimensions and weights			
	, , , , , , , , , , , , , , , , , , ,		
Depth	50 mm	Depth (inches)	1.9685 inch
Height	446 mm	Height (inches)	17.559 inch
Width	200 mm	Width (inches)	7.874 inch
Net weight	528 g		
Environmental Product Com	pliance		
B. U.S. S. J. S.			
RoHS Compliance Status	Compliant with exem	ption	
RoHS Exemption (if applicable/know	<u>'</u>		
REACH SVHC	Lead 7439-92-1		
SCIP	1eacbb3e-7931-4eb	b-9179-f29fd9b50028	
Technical data			
Description of article	Foam inlay tester		
Description of article	Foam may tester		
Tool chest			
Assembly	with tools		
	1		1
Classifications			
Classifications			
	EC011819	ETIM 7.0	EC011819
Classifications ETIM 6.0 ETIM 8.0	EC011819 EC011819	ETIM 7.0 ETIM 9.0	EC011819 EC011819
ETIM 6.0			
ETIM 6.0 ETIM 8.0	EC011819	ETIM 9.0	EC011819

ECLASS 15.0

21-07-04-12

ECLASS 14.0

Catalogue status / Drawings 2

TC INL THIRD 7



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Non-contact magnetic field tester

- · Reacts from a distance of 4 mm
- for testing operation of solenoid valves, relays, coils and contactors
- all magnetic fields can be tested
- · Visual and acoustic indication
- including a flashlight function

General ordering data

Туре	VT M	Version
Order No.	<u>2436680000</u>	Testing tools, Non-contact magnetic field tester
GTIN (EAN)	4050118450019	
Qty.	1 ST	

Non-contact voltage tester

- Reacts from a distance of 4 mm
- No current flow necessary thanks to capacitive method
- Detects concealed broken wires with a tolerance of just a few millimetres
- Detects voltage-conducting wires in sockets, cable reels, distributors, etc.
- Display: visual or both visual and acoustic
- including a flashlight function with the VT LCL

General ordering data

Туре	VT LCL	Version
	2436670000	Testing tools, Cable detector
GTIN (EAN)	4050118450033	
Qty.	1 ST	

with LCD Display

The main function of the voltage tester is to establish if voltage is present. A 2-pole voltage tester is the only approved testing instrument that fulfils the requirements of work protection regulations.

- with LCD-Display
- acc. to VDE standard,
- high peak voltage strength
- the right tester for every application

General ordering data

Туре	VT DIGI PRO	Version
Order No.	<u>9918870000</u>	Testing tools, 2-pole voltage tester
GTIN (EAN)	4032248405756	
Qty.	1 ST	
- 1.7.		

Creation date 26.11.2025 10:53:15 MEZ

Catalogue status / Drawings 3