HSS 1.6-4.8 EL W100M

The heat-shrinkable sleeve is printable on 2 sides and can be used for marking and insulating cables and wires. The flexible, heat-shrink material enables a firm, perfect fit around the conductor and therefore saves space.

General ordering data

Order No.	2724710000
Type	HSS 1.6-4.8 EL W100M
GTIN (EAN)	4050118819328
Qty.	1 items

HSS 1.6-4.8 EL W100M

Technical data

Approvals

ROHS	Conform

Dimensions and weights

Depth	0.77 mm		Depth (inches)	0.0303 inch
Width	7.6 mm		Width (inches)	0.2992 inch
Length	100000 mm		Length (inches)	3937 inch
Net weight	570 g			

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

General data

Type of printing	neutral		Width	7.6 mm
Operating temperature range, max.	135 °C		Operating temperature range, min.	-55 °C
Colour	white		Halogen	Yes
Length	100000 mm		Basic material	Polyolefine
Printed characters	without			

Conductor and cable markers

Halogen	Yes		Conductor cross-section, max.	4 mm²
Conductor cross-section, min.	0.75 mm²		Conductor O.D., max.	4.8 mm
Conductor O.D., min.	1.6 mm			

Classifications

ETIM 8.0	EC001530		ETIM 9.0	EC001530
ETIM 10.0	EC001530		ECLASS 14.0	27-28-11-02
ECLASS 15.0	27-28-11-02			