HDC C COAX 50 M

Crimps provide a electrical and mechanical connection between wire and contact that is both secure and reliable. The optimal crimp connection is gas-tight and corrosion-resistant.

General ordering data

Version	Male, gold, 0.14 - 0 mm²
Order No.	2748670000
Type	HDC C COAX 50 M
GTIN (EAN)	4050118890662
Qty.	10 items

HDC C COAX 50 M

Technical data

Approvals

Approvals	CE
ROHS	Conform

Dimensions and weights

Length	26.8 mm	Length (inches)	1.0551 inch
Net weight	2.04 g		

Temperatures

Limit temperature	-55 °C ... 135 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c
REACH SVHC	Lead 7439-92-1
SCIP	6eabd5ae-2d6b-409e-8bdf-87c27ee10e40

General data

Contact diameter, male Ø	4.8 mm	Stripping length, rated connection	2.5 mm
Type of connection	Solder connection	Version insert	COAX
Colour	gold	Conductor cross-section, max.	0 mm²
Conductor cross-section, min.	0.14 mm²	Surface finish	gold
Plugging cycles	≥ 500	Type	Male
Basic material	Copper alloy	Series	ModuPlug
Production methods	turned	Cross-section for connected wire	0.14 - 0 mm²

Classifications

ETIM 8.0	EC000796	ETIM 9.0	EC000796
ETIM 10.0	EC000796	ECLASS 14.0	27-44-02-04
ECLASS 15.0	27-44-02-04		

HDC C COAX 50 M

Accessories

CTX / HTG / HTX

Crimping tools for coaxial connectors
• Ratchet guarantees precise crimping
• Release option in the event of incorrect operation

General ordering data

Type	HTG 174	Version	
Order No.	9012410000	Pressing tool, Crimping tool for contacts, Hexagonal crimp	
GTIN (EAN)	4008190009434		
Qty.	1 ST		

Electrical modules

Flexible
The four module sizes make for individual plug solutions that save a huge amount of space. The smaller pitch translates into an optimised design too.

General ordering data

Type	HDC MCOAX 4 MC	Version	
Order No.	2748540000	Module, 48 V, 1.5 A, Number of poles: 4, Crimp connection, Male,	
GTIN (EAN)	4050118890754	Required plug-in slots: 1	
Qty.	5 ST		

Creation date 10.03.2026 12:44:22 MEZ