

**HDC C COAX 75 F**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)



Crimps provide a electrical and mechanical connection between wire and contact that is both secure and reliable. The optimal crimp connection is gas-tight and corrosion-resistant.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Version    | Female, gold               |
| Order No.  | <a href="#">2748680000</a> |
| Type       | HDC C COAX 75 F            |
| GTIN (EAN) | 4050118890655              |
| Qty.       | 10 items                   |

**HDC C COAX 75 F**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data**

**Approvals**

Approvals



ROHS Conform

**Dimensions and weights**

|            |        |                 |             |
|------------|--------|-----------------|-------------|
| Length     | 23 mm  | Length (inches) | 0.9055 inch |
| Net weight | 2.11 g |                 |             |

**Temperatures**

Limit temperature -55 °C ... 135 °C

**Environmental Product Compliance**

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| RoHS Compliance Status               | Compliant with exemption             |
| RoHS Exemption (if applicable/known) | 6c                                   |
| REACH SVHC                           | Lead 7439-92-1                       |
| SCIP                                 | 6eabd5ae-2d6b-409e-8bdf-87c27ee10e40 |

**General data**

|                          |                   |                                    |        |
|--------------------------|-------------------|------------------------------------|--------|
| Contact diameter, male Ø | 4.8 mm            | Stripping length, rated connection | 2.5 mm |
| Type of connection       | Solder connection | Version insert                     | COAX   |
| Colour                   | gold              | Surface finish                     | gold   |
| Plugging cycles          | ≥ 500             | Type                               | Female |
| Basic material           | Copper alloy      | Production methods                 | turned |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 8.0    | EC000796    | ETIM 9.0    | EC000796    |
| ETIM 10.0   | EC000796    | ECLASS 14.0 | 27-44-02-04 |
| ECLASS 15.0 | 27-44-02-04 |             |             |