


**APGTB 1.5 FT 3C/1 RD****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Some applications demand for a pluggable, modular solution to be more flexible or to facilitate the installation. Where complete functional units have to be prefabricated or replaced, modular and flexible connection systems are required. Our pluggable terminal blocks can be quickly assembled and are completely factory tested.

**General ordering data**

|            |  |
|------------|--|
| Version    | Plug-in modular terminals, PUSH IN, 2.5 mm <sup>2</sup> , 500 V, 17.5 A, red |
| Order No.  | <a href="#">2762010000</a>   |
| Type       | APGTB 1.5 FT 3C/1 RD   |
| GTIN (EAN) | 4064675012962  |
| Qty.       | 50 items   |

## APGTB 1.5 FT 3C/1 RD

Weidmüller Interface GmbH & Co. KG  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Technical data

## Approvals

Approvals



ROHS Conform

UL File Number Search [UL Website](#)

Certificate No. (cURus) E60693

## Dimensions and weights

|            |         |                 |             |
|------------|---------|-----------------|-------------|
| Depth      | 33.5 mm | Depth (inches)  | 1.3189 inch |
| Height     | 62 mm   | Height (inches) | 2.4409 inch |
| Width      | 3.5 mm  | Width (inches)  | 0.1378 inch |
| Net weight | 4.7 g   |                 |             |

## Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C         |                                  |        |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Material data

|                                |        |                           |     |
|--------------------------------|--------|---------------------------|-----|
| Basic material                 | Wemid  | Colour                    | red |
| Colour of operational elements | orange | UL 94 flammability rating | V-0 |

## Rating data IECEx/ATEX

|                                |                     |                                 |                     |
|--------------------------------|---------------------|---------------------------------|---------------------|
| Certificate No. (ATEX)         | TUEV16ATEX7940U     | Certificate No. (IECEX)         | IECEXTUR16.0046U    |
| Wire cross section max. (ATEX) | 1.5 mm <sup>2</sup> | Wire cross section max. (IECEX) | 1.5 mm <sup>2</sup> |

## System specifications

|                               |     |                                     |       |
|-------------------------------|-----|-------------------------------------|-------|
| End cover plate required      | Yes | Number of potentials                | 1     |
| Number of levels              | 1   | Number of clamping points per level | 3     |
| Number of potentials per tier | 1   | Levels cross-connected internally   | No    |
| PE connection                 | No  | Mounting rail                       | TS 35 |
| N-function                    | No  | PE function                         | No    |
| PEN function                  | No  |                                     |       |

## Additional technical data

|                  |         |                          |     |
|------------------|---------|--------------------------|-----|
| Open sides       | right   | Snap-on                  | No  |
| Type of fixing   | Snap-on | Explosion-tested version | Yes |
| Type of mounting | TS 35   |                          |     |

## Conductors for clamping (additional connection)

Connection type, additional connection pluggable

**APGTB 1.5 FT 3C/1 RD**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data**

**Conductors for clamping (rated connection)**

|   |                     |   |                      |
|---|---------------------|---|----------------------|
| Gauge to IEC 60947-1  | A1                  | Wire connection cross section AWG, max.   | AWG 14               |
| Connection direction  | top                 | Stripping length  | 8 mm                 |
| Type of connection  | PUSH IN             | Number of connections   | 3                    |
| Clamping range, max.  | 1.5 mm <sup>2</sup> | Clamping range, min.  | 0.14 mm <sup>2</sup> |
| Blade size  | 0.4 x 2.0 mm        | Wire connection cross section AWG, min.   | AWG 26               |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 1 mm <sup>2</sup>   | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.14 mm <sup>2</sup> |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 1.5 mm <sup>2</sup> | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.14 mm <sup>2</sup> |
| Wire connection cross section, finely stranded, max.                                    | 1.5 mm <sup>2</sup> | Wire connection cross section, finely stranded, min.                                    | 0.14 mm <sup>2</sup> |
| Connection cross-section, stranded, max.  | 1.5 mm <sup>2</sup> | Connection cross-section, stranded, min.  | 0.14 mm <sup>2</sup> |
| Wire connection cross-section, solid core, max.   | 1.5 mm <sup>2</sup> | Wire connection cross-section, solid core, min.   | 0.14 mm <sup>2</sup> |

**General**

|   |        |   |        |
|---|--------|---|--------|
| Wire connection cross section AWG, max. | AWG 14 | Wire connection cross section AWG, min. | AWG 26 |
| Mounting rail                           | TS 35  |   |        |

**Rating data**

|                                 |                     |  |         |
|---------------------------------|---------------------|--|---------|
| Rated cross-section             | 2.5 mm <sup>2</sup> | Rated voltage                                | 500 V   |
| Rated DC voltage                | 500 V               | Nominal current                              | 17.5 A  |
| Current at maximum wires        | 17.5 A              | Volume resistance according to IEC 60947-7-x | 1.83 mΩ |
| Rated impulse withstand voltage | 6 kV                | Power loss in accordance with IEC 60947-7-x  | 0.56 mW |
| Surge voltage category          | III                 | Pollution severity                           | 3       |

**UL rating data**

|  |        |  |        |
|--|--------|--|--------|
| Conductor size Factory wiring max. (cURus) | 14 AWG | Voltage size B (cURus)                     | 300 V  |
| Voltage size D (cURus)                     | 600 V  | Certificate No. (cURus)                    | E60693 |
| Conductor size Field wiring min. (cURus)   | 26 AWG | Conductor size Factory wiring min. (cURus) | 26 AWG |
| Current size B (cURus)                     | 13 A   | Voltage size C (cURus)                     | 300 V  |
| Current size C (cURus)                     | 13 A   | Current size D (cURus)                     | 5 A    |
| Conductor size Field wiring max. (cURus)   | 14 AWG |  |        |

**Classifications**


|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 8.0    | EC000897    | ETIM 9.0    | EC000897    |
| ETIM 10.0   | EC000897    | ECLASS 14.0 | 27-25-01-17 |
| ECLASS 15.0 | 27-25-01-17 |             |             |

**APGTB 1.5 FT 3C/1 RD**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**



## APGTB 1.5 FT 3C/1 RD

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

### Plugs



The plugs for our WeiCoS-System are available for all different connection systems. The product range includes preassembled connectors from 1 to 10 poles and the possibility of an individual assembly. This ensures maximum flexibility for every application. The customized accessories increase the safety and protection against environmental influences.

### General ordering data

|            |                            |   |  |
|------------|----------------------------|---|--|
| Type       | APGCE                      | Version   |  |
| Order No.  | <a href="#">1514490000</a> | Coding element (terminal), Wemid, orange, Width: 3.3 mm |  |
| GTIN (EAN) | 4050118321906              |   |  |
| Qty.       | 50 ST                      |   |  |

### Testadapter and testsockets



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

### General ordering data

|            |                            |  |  |
|------------|----------------------------|--|--|
| Type       | FZS 2/4 RT/80 SAKT4        | Version  |  |
| Order No.  | <a href="#">1276300000</a> | Plug (terminal), Plug-in connection, 2 mm <sup>2</sup> , Number of connections: 2, |  |
| GTIN (EAN) | 4008190026080              | Number of poles: 1, Width: 9 mm  |  |
| Qty.       | 20 ST                      |  |  |