

ZQV 4N/10 BK



Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

Version	Cross-connector (terminal), Plugged, black, 32 A, Number of poles: 10, Pitch in mm (P): 6.10, Insu- lated: Yes, Width: 58.7 mm	
Order No.	<u>2810830000</u>	
Туре	ZQV 4N/10 BK	
GTIN (EAN)	4064675283447	
Qty.	20 items	



ZQV 4N/10 BK



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Approvals					
ROHS	Conform				
Dimensions and weights					
	07.05	D #1 (* 1)	4.4004: 1		
Depth	27.95 mm	Depth (inches)	1.1004 inch		
Height Width	2.8 mm 58.7 mm	Height (inches)	0.1102 inch 2.311 inch		
Net weight	7.35 g	Width (inches)	2.3 11 111011		
Temperatures	7.55 g				
Temperatures					
Storage temperature	-25 °C55 °C	Ambient temperature	-5 °C40 °C		
Operating temperature	-60 °C130 °C	Continuous operating temp., min.	-60 °C		
Continuous operating temp., max.	130 °C				
Environmental Product Cor	npliance				
RoHS Compliance Status	Compliant without ex	Compliant without exemption			
REACH SVHC	No SVHC above 0.1 wt%				
Material data					
Basic material	Wemid	Colour	black		
UL 94 flammability rating	V-0				
Additional technical data					
Type of fixing	Plugged	Explosion-tested version	Yes		
Dimensions					
Pitch in mm (P)	6.10 mm				
General					
Number of poles	10				
Rating data					
Rated voltage	400 V	Nominal current	32 A		
Important note	400 V	Nonlinal current	32 A		
important note					
Product information	Due to stability and temperature reasons It is only possible to break out 60% of contact elements. The usage of cross connectors reduces the rated voltage to 400VThe voltage reduced to 25V if cu cross connection with blank cut edges are used.				
Classifications					
ETIMA	EC000489	ETIM 9.0	EC000489		
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	LIIIVI J.U	LC000403		
ETIM 8.0 ETIM 10.0	EC000489	ECLASS 14.0	27-25-03-03		

Creation date 03.12.2025 11:56:39 MEZ

Catalogue status / Drawings 2