## SD ELEC PRO

Test instruments are indispensable when installing, servicing and repairing electrical systems and equipment. Weidmüller has a full range of test devices, including voltage testers, clamp-on meters and power socket/circuit-breaker testers. Weidmüller always takes into account the wishes and experience of users in its development and design work, which means that Weidmüller devices are tailored to the needs of practical applications and are extremely reliable.

## General ordering data

| | |
|---|---|
| Version | Voltage testers, No |
| Order No. | 2855000000 |
| Type | SD ELEC PRO |
| GTIN (EAN) | 4064675530343 |
| Qty. | 1 items |

Creation date 11.03.2026 03:31:46 MEZ

## SD ELEC PRO

## Technical data

### Approvals

| | |
|---|---|
| ROHS | Conform |

### Dimensions and weights

| | | | |
|---|---|---|---|
| Depth | 22.2 mm | Depth (inches) | 0.874 inch |
| Width | 154.1 mm | Width (inches) | 6.0669 inch |
| Length | 154 mm | Length (inches) | 6.063 inch |
| Diameter | 22.2 mm | Net weight | 29.92 g |

### Environmental Product Compliance

| | |
|---|---|
| RoHS Compliance Status | Not affected |
| REACH SVHC | No SVHC above 0.1 wt% |

### Technical data

| | |
|---|---|
| Description of article | Srewdriver Voltagetester |

### Measuring and testing devices

| | | | |
|---|---|---|---|
| Blade width (B) | 3 mm | Load switchable | No |
| AC voltage measuring range | 100-250 V | Working temperature, max. | 50 °C |
| Working temperature, min. | -10 °C | Frequency range, max. | 500 Hz |
| Frequency range, min. | 50 Hz | Display | Visual |
| Blade length | 63 mm | Phase sequence display | No |
| Continuity test | No | Test probe protection GS 38 | No |
| Test probe illumination | No | HOLD function | No |

### Classifications

| | | | |
|---|---|---|---|
| ETIM 8.0 | EC000494 | ETIM 9.0 | EC000494 |
| ETIM 10.0 | EC000494 | ECLASS 14.0 | 27-20-03-08 |
| ECLASS 15.0 | 27-20-03-08 | | |