


SFC-DS 1/12 MC NE GE**Weidmüller Interface GmbH & Co. KG**Klingenbergstraße 26
D-32758 Detmold
Germanywww.weidmueller.com

SFC – SlimFix Clip MultiCard with two labelling fields
For conductor markers, it is often required to quickly read the start and destination designation of the respective conductor. Here it makes sense to print both data directly on a marker.

The new SFC-DS markers are designed as MultiCards and are suitable for direct printing with our PrintJet printing system. Their two labelling areas allow multiple data to be printed on a single marker. The print data can be imported directly from CAE projects into the M-Print® PRO marking software. After printing, the markers are placed around the conductor and securely fixed with a special locking mechanism.

General ordering data

Version	Conductor and cable markers, 12 x 5.2 mm, yellow
Order No.	2905060000
Type	SFC-DS 1/12 MC NE GE
GTIN (EAN)	4099986918641
Qty.	200 items

SFC-DS 1/12 MC NE GE

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

ROHS	Conform
------	---------

Dimensions and weights

Depth	4 mm	Depth (inches)	0.1575 inch
Height	12 mm	Height (inches)	0.4724 inch
Width	5.2 mm	Width (inches)	0.2047 inch
Net weight	0.31 g		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption		
REACH SVHC	No SVHC above 0.1 wt%		
Product Carbon Footprint	Cradle to gate	0.003 kg CO2 eq.	

General data

Type of printing	neutral	Version	with snap-in foot
Width	5.2 mm	UL 94 flammability rating	UL 94, V-2
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Colour	yellow	Halogen	No
Basic material	Polyamide 66	Printed characters	without
Size of labelling field	11 x 3.2 mm	Number per roll	40

Conductor and cable markers

Halogen	No	Conductor cross-section, max.	2.5 mm ²
Conductor O.D., max.	3.3 mm	Conductor O.D., min.	2 mm
Cross-section for connected wire	2.5 mm ²		

Classifications

ETIM 8.0	EC001530	ETIM 9.0	EC001530
ETIM 10.0	EC001530	ECLASS 14.0	27-28-11-02
ECLASS 15.0	27-28-11-02		

Drawings

