

PV BSS DL**Weidmüller Interface GmbH & Co. KG**Klingenbergsstraße 26
D-32758 Detmold
Germanywww.weidmueller.com

Field-wirable AC connectors for PV inverters with Plug & Play

- Due to the robust design and the choice of UV-resistant materials, the AC connector can also be used under adverse environmental conditions such as vibrations and strong sunlight
- The three-phase connector solution has been optimized for cable cross-sections of up to 16 mm², which significantly reduces energy losses
- The compact design gives you high performance with a small footprint
- Installation is fast and efficient and enables convenient handling in the field

General ordering data

Order No.	2920120000
Type	PV BSS DL
GTIN (EAN)	4099986583016
Qty.	20 items

PV BSS DL

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

Approvals



RoHS Conform

Dimensions and weights

Net weight 11.4 g

Temperatures

Continuous operating temp., min. -40 °C Continuous operating temp., max. 105 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	Potassium perfluorobutane sulfonate 29420-49-3
SCIP	dd4ee0b3-e949-42dd-9269-5de96565d3fd

General Data

Colour	black	Pollution severity	3
Basic material	Plastic		

Technical data

Protection degree	IP65, in closed state, IP2x open, IP67, IP68	Pollution severity	3
-------------------	--	--------------------	---

Guarantee

Time interval 2 years

Classifications

ETIM 8.0	EC002928	ETIM 9.0	EC002928
ETIM 10.0	EC002928	ECLASS 14.0	22-57-02-92
ECLASS 15.0	22-57-02-92		