


THM PV 27/18 TR**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



UV-radiation causes high stress and aging of plastic in the outdoor application.

Our new THM PV labels resist these influences and are extremely durable in outdoor use.

Compact designed packaging are our TABPACK-PV.

These are-printed warning labels, which should be a part of the basic equipment of a professional photovoltaic builder.

Your advantages at a glance:

- Weathering resistance tested according to ISO DIN EN ISO 4892-2:2013 table 3, procedure A cycle 1 at 5000 hours
- Individually labeled with the M-Print® PRO
- Easy and fast printing with the THM MultiMark

General ordering data

Version	ClipCard, Device markers, 17.3 x 26.6 mm, Transparent
Order No.	2969160000
Type	THM PV 27/18 TR
GTIN (EAN)	4099986783904
Qty.	450 items
Packaging	Reel

THM PV 27/18 TR

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

ROHS	Conform
------	---------

Dimensions and weights

Depth	0.05 mm	Depth (inches)	0.002 inch
Height	17.3 mm	Height (inches)	0.6811 inch
Width	26.6 mm	Width (inches)	1.0472 inch
Net weight	0.1 g		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

General data

Adhesive	Polyacrylate adhesive	Type of printing	neutral
Printing method	Thermal transfer	Version	Self-adhesive
Width	26.6 mm	UL 94 flammability rating	V-0
Operating temperature range, max.	-50 °C	Operating temperature range, min.	110 °C
Colour	Transparent	Halogen	Yes
Basic material	Vinyl film	Printed characters	without
Number per roll	450		

Conductor and cable markers

Halogen	Yes
---------	-----

Device markers

Halogen	Yes
---------	-----

Classifications

ETIM 8.0	EC001288	ETIM 9.0	EC001288
ETIM 10.0	EC001288	ECLASS 14.0	27-28-11-04
ECLASS 15.0	27-28-11-04		

