

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





## Weidmüller Industrial Security Routers

- Secure networks
  - · Stateful packet inspection Firewall
  - IP/Port- forwarding
  - Network segmentation
- Easy integration of machine networks into manufacturing networks through 1: 1 NAT
- Secure and easy remote maintenance with Weidmüller u-link remote access service
- Enable modular and future proof network architectures with static and dynamic routing
- Secure communication over the Internet by using IPsec and OpenVPN
- Reliable internet connection, even without on-site internet access, thanks to integrated 4G/LTE cellular modem
- Full flexibility thanks to Fast Ethernet and Gigabit Ethernet interfaces ranging from 2 up to 4 ports.

#### **General ordering data**

Version	Security/NAT/VPN/U-link Router, with integrated multi-band modem (4G/3G), Global-model, Gigabit Ethernet, 4x RJ45 10/100/1000BaseT(X), DNV, IP20, -25 °C70 °C
Order No.	<u>2990440000</u>
Туре	IE-SR-4GT-LTE/4G-USEMEA-M
GTIN (EAN)	4099986863514
Qty.	1 items

1





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

Approvals



ROHS Conform

## **Dimensions and weights**

Depth	115 mm	Depth (inches)	4.5275 inch
Height	150 mm	Height (inches)	5.9055 inch
Width	55 mm	Width (inches)	2.1654 inch
Net weight	660 g		

#### **Temperatures**

Storage temperature	-40 °C85 °C	Operating temperature	-25 °C70 °C
Humidity	5 - 90 %, no condensation		

# **Environmental Product Compliance**

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6al, 6c, 7a, 7cl, 7cll
REACH SVHC	Lead 7439-92-1, 2-Benzyl-2-dimethylamino-4-morpholinobutyrophenone 119313-12-1, 2-Methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one 71868-10-5, 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol 119-47-1, Lead monoxide 1317-36-8, Lead titanium trioxide 12060-00-3, N, N-dimethylacetamide 127-19-5

#### Mobile radio interface

Transmission rate mobile radio	LTE category	CAT 13
	Download rate, max.	400 Mbit/s
	Upload rate, max.	150 Mbit/s
Mode of operation	Permanent connection, Manual connection control via web interface, Manual connection control via API or SMS, Fallback	
Wireless module	multi-band modem (4G/3G)	
Frequency band		3, B4, B5, B7, B8, B12, B13, B14, B18, B19, B20, B25, B26, B41, B42, B43, B48, B66, B71, 3G UMTS/HSPA+: B1, B2, B4,

#### **EMC** conformity and approvals

EMC standards	EN 61000-6-4, EN 61000-6-2, FCC Part 15 Class B	Vibration	according to IEC 60068-2-6
Shock	according to IEC 60068-2-27	Ship use	DNV
Safety standard	EN 62368-1, EN 62311	Security standard	EN 18031-1

#### **Environmental conditions**

Operating temperature, max.	70 °C	Operating temperature, min.	-25 °C
Humidity	5 - 90 %, no condensation	Storage temperature, max.	85 °C
Storage temperature, min.	-40 °C		

Creation date 27.11.2025 06:35:11 MEZ





#### Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

Time interval	3 years		
Time interval	3 years		1
Interfaces			
RJ45 ports	10/100/1000BaseT(X), auto negotiation, Full-/half- duplex mode, Auto MDI/ MDI-X port	Number of ports	4x RJ45 10/100/1000BaseT(X)
Function reset button	Restoration of factory settings	Digital outputs	VPN-active: indicates an active VPN connection (24 V out), Alarm: indicates a configurable network state or fault (24 V out)
Digital inputs	galvanically isolated, Cut: physically disconnects (Link Down) the WAN port (24 V in), Trigger pre-configured packet filter rules (24 V in), VPN-initiate: establishes a pre-configured VPN connection (24 V in)	SCM-Card slot type	Smart Card (ID-000 format), Save and restore the configuration using smart card (memory chip)
SIM-Card slot type	Mini-SIM (ID-000 format)	Connector for external antennas	2x SMA female
USB port	USB 2.0 interface for firmware update or restoration of the device configuration via USB flash drive	Serial port	1x RS-485, 2-wire, galvanically isolated, 1 removable 3-pin terminal block
Number of SIM-Card slots	1	Number of SCM-Card slots	1
LED indicator	Power: indicates power supply status, boot-up process, firmware update process, Status: indicates system status, VPN: indicates VPN tunnel status, Port LED: Link/ACT, Speed (RJ45 port)		
Management features			
Device configuration	Webbrowser (HTTP/ HTTPS), SNMP v3, Windows tool	Monitoring function	SNMP v3, Syslog, Event based warning via E-Mail, Event based warning via relay, Event based warning via SMS
IP-address management	Static, DHCP-Client, DHCP- Server (pool-based), DNS- Relay	Time synchronization management	NTP server, NTP client
Power supply			
Reverse polarity protection Supply voltage	Yes Galvanically isolated, 24 V D	С	
Overload current protection	Yes		
Connection type	1 removable 3-pin terminal b		
Voltage supply range	Voltage type	DC	
	Voltage, min.	19.2 V	
	Voltage, max.	28.8 V	
Current consumption	Voltage	24 V	
	Current	1.5 A	







#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

	Voltage type	DC	
Routing Features			
NAT functions	Source / Destination NAT (Port / Host / Network)	Firewall functions	Stateful Packet Inspection Firewall (Layer-3), Transparent bridge mode (4-port switch with additional Layer-2 filter)
VPN functions	u-link client, OpenVPN (Server or Client), IPSec (Initiator or Responder)	Routing functions	IPv4 routing, IPv4 routing extended (each interface (LAN, WAN, optional cellular) can be configured as separate IP network), Static and dynamic IP Routing, RIPv2 / OSPF
Technical data			
Housing main material	Aluminium	Type of mounting	DIN rail
Protection degree	IP20	Speed	Gigabit Ethernet
<b>Technology</b> Standard	IEEE 802.3 for 10BASE-T, IEEE 802.3u for 100BASE- TX, IEEE 802.3ab for 1000BASE-T		
Important note			
Product information		ase check the compatibility list f the SCM card IE-EBR-SMARTCA	
Classifications			
		=======================================	
ETIM 6.0	EC001478	ETIM 7.0	EC001478
ETIM 8.0	EC001478	ETIM 9.0	EC001478
ETIM 10.0	EC001478	ECLASS 9.0	19-17-01-03
ECLASS 9.1	19-17-01-03	ECLASS 10.0	19-17-04-05
ECLASS 11.0	19-17-04-05	ECLASS 12.0	19-17-04-05
ECLASS 13.0	19-17-04-05	ECLASS 14.0	19-17-04-05
ECLASS 15.0	19-17-04-05		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### Antennas and antenna accessories (coax cables and mounts)



Antennas and antenna accessories (coax cables and mounts)

- State-of-the-art antennas
- Industry proven
- Robust design (up to IP67 protection)
- For outdoor and indoor use
- Latest technology support
- Up to Wi-Fi 6 and Wi-Fi 6E (2.4 GHz, 5 GHz, 6 GHz)
- Up to 5G (NR) support (700 MHz 3.8 GHz)
- Also support for other technologies (e.g. Bluetooth, GNSS, etc.)
- · Appropriate coax cables at different lengths
- Suitable pole and wall mounts

#### **General ordering data**

Туре	IE-ANT-CELL/WL-MB-MIMO	Version
Order No.	<u>2788090000</u>	Omni-directional antenna, Cellular antenna, Wi-Fi antenna, Up to 5G
GTIN (EAN)	4064675066354	(NR), Up to Wi-Fi 6 & 6E (IEEE802.11ax), Linear, Vertical, 2x SMA
Qty.	1 ST	male, 2x RP-SMA female, IP67, Impedance: 50 $\Omega$
Туре	IE-ANT-CELL-MIMO-DO-SMAM	Version
Order No.	<u>2788120000</u>	Omni-directional antenna, Cellular antenna, Up to 5G (NR), Linear,
GTIN (EAN)	4064675066385	Vertical, $2x$ SMA male, IP67, Impedance: $50~\Omega$
Qty.	1 ST	
Туре	IE-ANT-CELL-SISO-EO-SMAM	Version
Type Order No.	IE-ANT-CELL-SISO-EO-SMAM 2788130000	Version Omni-directional antenna, Cellular antenna, Up to 5G (support for
Order No.	2788130000	Omni-directional antenna, Cellular antenna, Up to 5G (support for
Order No. GTIN (EAN)	2788130000 4064675066392	Omni-directional antenna, Cellular antenna, Up to 5G (support for frequencies below 2.7 GHz, e.g., bands n1, n2, n28), Vertical, SMA
Order No. GTIN (EAN) Qty.	2788130000 4064675066392 1 ST	Omni-directional antenna, Cellular antenna, Up to 5G (support for frequencies below 2.7 GHz, e.g., bands n1, n2, n28), Vertical, SMA male, IP66, Impedance: $50~\Omega$
Order No. GTIN (EAN) Oty. Type	2788130000 4064675066392 1 ST IE-ANT-CELL-SISO-LO-NF	Omni-directional antenna, Cellular antenna, Up to 5G (support for frequencies below 2.7 GHz, e.g., bands n1, n2, n28), Vertical, SMA male, IP66, Impedance: $50~\Omega$
Order No. GTIN (EAN) Qty. Type Order No.	2788130000 4064675066392 1 ST IE-ANT-CELL-SISO-LO-NF 2788150000	Omni-directional antenna, Cellular antenna, Up to 5G (support for frequencies below 2.7 GHz, e.g., bands n1, n2, n28), Vertical, SMA male, IP66, Impedance: $50\Omega$ Version  Omni-directional antenna, Cellular antenna, Up to 5G (NR), Vertical, N



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# Accessories

#### **u-link Remote Access Service**



The Weidmüller u-link remote access service offers an easy possibility to securely access ethernet devices in a remote network.

With the u-link VPN Server as the central meeting point server, the VPN clients (service PC and Weidmüller u-link client devices) always connect outbound and thus conform to the typical IT security requirements. Separate database and server instances are used for each u-link customer account (secure client isolation) to ensure data integrity.

Communication between the u-link VPN server and remote clients (service PCs and u-link client devices) takes place via a certificate-protected openVPN connection. The u-link creed is "configuration instead of programming" the use is intuitive and does not require expert knowledge.

#### Featureset:

- 1-click VPN remote access for service PC's
- easyAccess: web, rdp or vnc connections to remote hosts fully browser based for use with tablet or smartphone
- Organization and Group Management
- Topologies including 3rd party end-devices
- Firmware management: Display of firmware status of all routers and the option of a time-controlled, automated firmware update
- Individual access rights: granular configuration of access rights to devices in the target network
- Extensive event log: Presentation of all activities in the u-link portal with extensive filter and export functions
- Password policy: Increased security through configurable specification of minimum requirements for password quality and validity period

Weidmüller offers the following usage variations and additional options for the u-link Remote Access Service: Basic version:

- Automatically assigned by registering at ulink.weidmueller.com
- Free use for 6 months, extended to 365 days when registering a new u-link client device
- Full featureset
- Unlimited users
- Max. 50 u-link capable devices (access points to a remote network)
- 1 simultaneous VPN connection
- No data or speed limitations (subject to normal market usage)

#### Extensions

- Additional 50/100/250/500/1000 or more u-link capable devices
- Additional simultaneous VPN connections
- China-VPN: secure and reliable VPN connection to and from China



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

## **General ordering data**

Туре	U-LINK-BASIC-EXTENSION	Version
Order No.	3024610000	License code for u-link Remote Access Service., Extends the period of
GTIN (EAN)		the basic license by 1 year.
Qty.	1 ST	
Туре	U-LINK-50-DEVICES-1Y	Version
Order No.	2870090000	License code for u-link Remote Access Service., Adds 50 additional
GTIN (EAN)		configurable u-link clients on Weidmüller hardware to the basic
Qty.	1 ST	license and extends the period of the basic license accordingly.
Туре	U-LINK-100-DEVICES-1Y	Version
Order No.	2870100000	License code for u-link Remote Access Service., Adds 100 additional
GTIN (EAN)		configurable u-link clients on Weidmüller hardware to the basic
Qty.	1 ST	license and extends the period of the basic license accordingly.
Туре	U-LINK-250-DEVICES-1Y	Version
Order No.	2870110000	License code for u-link Remote Access Service., Adds 250 additional
GTIN (EAN)		configurable u-link clients on Weidmüller hardware to the basic
Qty.	1 ST	license and extends the period of the basic license accordingly.
Туре	U-LINK-500-DEVICES-1Y	Version
Order No.	2870120000	License code for u-link Remote Access Service., Adds 500 additional
GTIN (EAN)		configurable u-link clients on Weidmüller hardware to the basic
Qty.	1 ST	license and extends the period of the basic license accordingly.
Туре	U-LINK-1000-DEVICES-1Y	Version
Order No.	2924220000	License code for u-link Remote Access Service., Adds 1000 additional
GTIN (EAN)		configurable u-link clients on Weidmüller hardware to the basic
Qty.	1 ST	license and extends the period of the basic license accordingly.
Туре	U-LINK-1-CONNECTION-1Y	Version
Order No.	<u>2870130000</u>	"VPN connection" licence code for u-link Remote Access Service. Can
GTIN (EAN)		be used as an additional VPN connection or to extend the period of a
Qty.	1 ST	VPN connection that has already been activated
Туре	U-LINK-CNSERVER-1Y	Version
Order No.	2870140000	License code for u-link Remote Access Service., Allows the use of the
GTIN (EAN)		server in China for a secure and reliable VPN connection to and from
Qty.	1 ST	China.

# Mounting kit for 19" rack assembly

• For assembling DIN rail-based devices on 19" racks



## **General ordering data**

Type	RM-KIT	Version
Order No.	1241440000	Kit for 19"-rack mounting
GTIN (EAN)	4050118029154	
Qty.	1 ST	

Creation date 27.11.2025 06:35:11 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### **Ethernet**



- Suitable for Cat. 5 (up to 100 MHz) and Cat. 6 (up to 250 MHz Class E)
- Suitable for PoE+ (according to IEEE 802.3at, IEEE 802.3bt Type 3 and 4)
- Protection of all wire pairs
- Connection via RJ45 sockets
- Metal housing

#### General ordering data

Type VDATA CAT6
Order No. 1348590000
GTIN (EAN) 4050118153002

Version

Terminal rail fixing, Surge protection, Cat.6, PoE, 802.3 bt at Type 1, 802.3 bt at Type 2, 802.3 bt at Type 3, 802.3 bt at Type 4

#### **Industrial Security Router**



Weidmüller Industrial Security Routers

- Secure networks
  - Stateful packet inspection Firewall
  - IP/Port- forwarding
  - Network segmentation
- Easy integration of machine networks into manufacturing networks through 1: 1 NAT
- Secure and easy remote maintenance with Weidmüller u-link remote access service
- Enable modular and future proof network architectures with static and dynamic routing
- Secure communication over the Internet by using IPsec and OpenVPN
- Reliable internet connection, even without on-site internet access, thanks to integrated 4G/LTE cellular modem
- Full flexibility thanks to Fast Ethernet and Gigabit Ethernet interfaces ranging from 2 up to 4 ports.

## **General ordering data**

 Type
 IE-EBR-SMARTCARD-SR
 Version

 Order No.
 2909820000
 Router smartcard,

 GTIN (EAN)
 4099986227361

 Qty.
 1 ST

Creation date 27.11.2025 06:35:11 MEZ