

PV XSTU06 BUOWM4C-C250**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The extension cable is used to connect several elements of a PV system, e.g. for the connection between PV panels, inverters and surge protection boxes. The cables are available in different connection variants.

General ordering data

Version	Photovoltaics, Y connector, Cable end open
Order No.	3010170250
Type	PV XSTU06 BUOWM4C-C250
GTIN (EAN)	4099986930322
Qty.	1 items

PV XSTU06 BUOWM4C-C250

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

ROHS	Conform
------	---------

Dimensions and weights

Net weight	1000 g
------------	--------

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c
REACH SVHC	Lead 7439-92-1

PV cable harnessing

PV cable version	Cable side	left
	Number	1
	Cable length	2500 mm
	Cable colour	black
	Cable cross section	6 mm ²
	Inline fuse integrated	No
	Version of cable end [In-Block]	free conductor end
	Connector version	WM4 C
	Type of plug-in contact	female
Rated DC voltage	1500 V	
Wire cross-section	6.00 mm ²	

Electrical characteristics

Rated DC voltage	1500 V
------------------	--------

Classifications

ETIM 8.0	EC001576	ETIM 9.0	EC001576
ETIM 10.0	EC001576	ECLASS 14.0	27-06-04-02
ECLASS 15.0	27-06-04-02		