


Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com



Some applications demand for a pluggable, modular solution to be more flexible or to facilitate the installation. Where complete functional units have to be prefabricated or replaced, modular and flexible connection systems are required. Our pluggable terminal blocks can be quickly assembled and are completely factory tested.

General ordering data

Version	Pluggable terminal, SNAP IN, blue, 2.5 mm ² , 24 A, 800 V, Number of connections: 6, Number of levels: 2, TS 35
Order No.	<u>3096150000</u>
Туре	SPGTB 2.5 2T 6C/2 BL
GTIN (EAN)	4099987120906
Qty.	50 items





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Approvals

Approvals



Dimensions and weights

Depth	52 mm	Depth (inches)	2.0472 inch
Height	115 mm	Height (inches)	4.5275 inch
Width	5.1 mm	Width (inches)	0.2008 inch
Net weight	0 g		

Temperatures

Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C	

Material data

Basic material	Wemid	Colour	blue	
Colour of operational elements	green	UL 94 flammability rating	V-0	

System specifications

End cover plate required	Yes	Number of potentials	2
Number of levels	2	Number of clamping points per level	3
Levels cross-connected internally	No	PE connection	No
Mounting rail	TS 35	N-function	No
PE function	No	PEN function	No

Additional technical data

Open sides	right	Snap-on	Yes	
Type of fixing	TS 35	Explosion-tested version	No	
Type of mounting	TS 35			

Conductors for clamping (additional connection)

Connection type, additional connection SNAP IN

Conductors for clamping (rated connection)

Gauge to IEC 60947-1	A2	Wire connection cross section AWG, max.	AWG 14
Connection direction	top	Stripping length	10 mm
Type of connection	SNAP IN	Number of connections	6
Clamping range, max.	2.5 mm ²	Clamping range, min.	0.34 mm ²
Blade size	0.6 x 3.5 mm	Wire connection cross section AWG, min.	AWG 22
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	2.5 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	0.34 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	2.5 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	0.34 mm ²
Wire connection cross section, finely stranded, max.	4 mm ²	Wire connection cross section, finely stranded, min.	0.34 mm ²

Creation date 01.12.2025 11:35:43 MEZ





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Connection cross-section, stranded, max.	2.5 mm ²	Connection cross-section, stranded, min. 0.34 mm ²
Wire connection cross-section, solid core, max.	2.5 mm ²	Wire connection cross-section, solid 0.34 mm² core, min.

General

Wire connection cross section AWG,	AWG 14	Wire connection cross section AWG,	AWG 22
max.		min.	
Standards	IEC 60947-7-1	Mounting rail	TS 35

Rating data

Rated cross-section	2.5 mm ²	Rated voltage	800 V
Rated DC voltage	800 V	Nominal current	24 A
Current at maximum wires	24 A	Standards	IEC 60947-7-1
Volume resistance according to IEC 60947-7-x	1.33 mΩ	Rated impulse withstand voltage	8 kV
Power loss in accordance with IEC 60947-7-x	0.77 mW	Pollution severity	3

Classifications

ETIM 7.0	EC000897	ETIM 8.0	EC000897
ETIM 9.0	EC000897	ETIM 10.0	EC000897
ECLASS 11.0	27-14-11-20	ECLASS 12.0	27-14-11-20
ECLASS 13.0	27-25-01-17	ECLASS 14.0	27-25-01-17
ECLASS 15.0	27-25-01-17		




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Drawings









Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Cross-connections









The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

General	ordering data	
Туре	ZQV 2.5N/10	Version
Order No.	<u>1527690000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118447989	10, Pitch in mm (P): 5.10, Insulated: Yes, Width: 48.7 mm
Qty.	20 ST	
Туре	ZQV 2.5N/10 BL	Version
Order No.	<u>1527880000</u>	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 10,
GTIN (EAN)	4050118448573	Pitch in mm (P): 5.10, Insulated: Yes, Width: 48.7 mm
Qty.	20 ST	
Туре	ZQV 2.5N/10 RD	Version
Order No.	<u>2108910000</u>	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 10,
GTIN (EAN)	4050118486018	Pitch in mm (P): 5.10, Insulated: Yes, Width: 48.7 mm
Qty.	20 ST	
Туре	ZQV 2.5N/2	Version
Order No.	<u>1527540000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118448467	2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm
Qty.	60 ST	
Туре	ZQV 2.5N/2 BL	Version
Order No.	<u>1527740000</u>	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 2,
GTIN (EAN)	4050118448658	Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm
Qty.	60 ST	
Туре	ZQV 2.5N/2 RD	Version
Order No.	<u>2108470000</u>	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 2,
GTIN (EAN)	4050118448542	Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm
Qty.	60 ST	
Туре	ZQV 2.5N/20	Version
Order No.	<u>1527720000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118447972	20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm
Qty.	20 ST	
Туре	ZQV 2.5N/20 BL	Version
Order No.	<u>1527890000</u>	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 20,
GTIN (EAN)	4050118448566	Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm
Qty.	20 ST	
Туре	ZQV 2.5N/20 RD	Version
Order No.	2108920000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 20,
GTIN (EAN)	4050118485899	Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm
Qty.	20 ST	
Туре	ZQV 2.5N/3	Version
Order No.	<u>1527570000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118448450	3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm
Qty.	60 ST	
	_	

Creation date 01.12.2025 11:35:43 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

-	70)/0.51/0.51	W. :
Туре	ZQV 2.5N/3 BL	Version
Order No.	1527770000	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 3,
GTIN (EAN)	4050118448641	Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm
Qty.	60 ST	
Туре	ZQV 2.5N/3 RD	Version
Order No.	2108690000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 3,
GTIN (EAN)	4050118448535	Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm
Qty.	60 ST	
Туре	ZQV 2.5N/4	Version
Order No.	<u>1527590000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118448443	4, Pitch in mm (P): 5.10, Insulated: Yes, Width: 18.1 mm
Qty.	60 ST	
Туре	ZQV 2.5N/4 BL	Version
Order No.	<u>1527780000</u>	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 4,
GTIN (EAN)	4050118448634	Pitch in mm (P): 5.10, Insulated: Yes, Width: 18.1 mm
Qty.	60 ST	
Туре	ZQV 2.5N/4 RD	Version
Order No.	2108700000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 4,
GTIN (EAN)	4050118448528	Pitch in mm (P): 5.10, Insulated: Yes, Width: 18.1 mm
Qty.	60 ST	
Туре	ZQV 2.5N/5	Version
Order No.	<u>1527620000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118448436	5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm
Qty.	20 ST	
Туре	ZQV 2.5N/5 BL	Version
Order No.	<u>1527790000</u>	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 5,
GTIN (EAN)	4050118448627	Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm
Qty.	20 ST	
Туре	ZQV 2.5N/5 RD	Version
Order No.	<u>2108710000</u>	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 5,
GTIN (EAN)	4050118448511	Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm
Qty.	20 ST	
Туре	ZQV 2.5N/50	Version
Order No.	<u>1527730000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118411362	50, Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm
Qty.	5 ST	
Туре	ZQV 2.5N/50 BL	Version
Order No.	1527920000	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 50,
GTIN (EAN)	4050118448559	Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm
Qty.	5 ST	
Туре	ZQV 2.5N/50 RD	Version
Order No.	2109000000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 50,
GTIN (EAN)	4050118486001	Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm
Qty.	5 ST	
Туре	ZQV 2.5N/6	Version
Order No.	<u>1527630000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118448429	6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm
Qty.	20 ST	
Туре	ZQV 2.5N/6 BL	Version
Order No.	<u>1527820000</u>	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 6,
GTIN (EAN)	4050118448610	Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm
Qty.	20 ST	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Туре	ZQV 2.5N/6 RD	Version
Order No.	2108720000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 6,
GTIN (EAN)	4050118448504	Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm
Qty.	20 ST	
Туре	ZQV 2.5N/7	Version
Order No.	1527640000	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118448412	7, Pitch in mm (P): 5.10, Insulated: Yes, Width: 33.4 mm
Qty.	20 ST	7, 11cm ii 11iii (1). 5. 15, iiisalacca. 165, waddi. 55.4 iiiii
Туре	ZQV 2.5N/7 BL	Version
Order No.	1527830000	
	4050118448603	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 7,
GTIN (EAN)		Pitch in mm (P): 5.10, Insulated: Yes, Width: 33.4 mm
Qty.	20 ST	v :
Type	ZQV 2.5N/7 RD	Version
Order No.	<u>2108810000</u>	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 7,
GTIN (EAN)	4050118448498	Pitch in mm (P): 5.10, Insulated: Yes, Width: 33.4 mm
Qty.	20 ST	
Туре	ZQV 2.5N/8	Version
Order No.	<u>1527670000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118448405	8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm
Qty.	20 ST	
Туре	ZQV 2.5N/8 BL	Version
Order No.	1527840000	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 8,
GTIN (EAN)	4050118448597	Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm
Qty.	20 ST	
Туре	ZQV 2.5N/8 RD	Version
Order No.	2108870000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 8,
GTIN (EAN)	4050118448481	Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm
Qty.	20 ST	
Туре	ZQV 2.5N/9	Version
Order No.	<u>1527680000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118447996	9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm
Qty.	20 ST	
Туре	ZQV 2.5N/9 BL	Version
Order No.	<u>1527870000</u>	Cross-connector (terminal), Plugged, blue, 24 A, Number of poles: 9,
GTIN (EAN)	4050118448580	Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm
Qty.	20 ST	
Туре	ZQV 2.5N/9 RD	Version
Order No.	2108900000	Cross-connector (terminal), Plugged, red, 24 A, Number of poles: 9,
GTIN (EAN)	4050118448474	Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm
Qty.	20 ST	
•	-	

Plugs



The plugs for our WeiCoS-System are available for all different connection systems. The product range includes preassembled connectors from 1 to 10 poles and the possibility of an individual assembly. This ensures maximum flexibility for every application. The customized accessories increase the safety and protection against environmental influences.

7



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Type	Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty.	1514490000 4050118321906 50 ST APGSR 2.5/4 2457580000 4050118472998 25 ST APGSR 2.5/4 - 4P 2457590000 4050118472967 25 ST	Coding element (terminal), Wemid, orange, Width: 3.3 mm Version Strain relief (terminal), Wemid, orange Version
GTIN (EAN) 4050 118321906 Ony, 50 ST Type APGSR 2.5/4 Version Order No. 2457580000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050 118472988 Ony, 25 ST Type APGSR 2.5/4 - 4P Version Order No. 2457580000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050 118472987 Ony, 25 ST Type APGSR 2.5/4 - 8P Version Order No. 2457580000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050 118472987 Ony, 25 ST Type APGSR 2.5/4 - 8P Version Order No. 2457580000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050 118472929 Ony, 25 ST Type APGL 2.5/4 Version Order No. 2457500000 Locking clips (terminal), Wemid, orange GTIN (EAN) 4050 118473100 Ony, 25 ST Type APGL 2.5/4 Version Order No. 15.14500000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050 11832100 Ony, 50 ST Type APG 2.5 Version Order No. 15.13830000 Pug. 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050 118321823 Ony, 50 ST Type APG 2.5 LBL Version Order No. 15.13840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050 118321820 Order No. 15.13840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050 118321810 Order No. 15.13840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, green GTIN (EAN) 4050 118321810 Order No. 15.13840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050 118321810 Order No. 15.13840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050 118321810 Order No. 15.13840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050 118321810 Order No. 15.13840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050 118321812 Order No. 15.13840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050 118321810 Order No. 15.13840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050 118321810 Order No. 15.13840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050 11832183000 Plug,	GTIN (EAN) Oty. Type Order No. GTIN (EAN) Oty. Type Order No. GTIN (EAN) Oty. Type Order No. GTIN (EAN) Oty.	4050118321906 50 ST APGSR 2.5/4 2457580000 4050118472998 25 ST APGSR 2.5/4 - 4P 2457590000 4050118472967 25 ST	Version Strain relief (terminal), Wemid, orange Version
QBy. 50 ST Version Order No. 2437580000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4060118472988 QNy. 25 ST Type APGSR 2.5/4 - 4P Version Order No. 2457580000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4060118472967 Ony. Ory. 25 ST Version Order No. 2457600000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4060118472929 Oly. Qly. 25 ST Version Order No. 2457500000 Locking clips (terminal), Wemid, orange GTIN (EAN) 4060118473100 Oly. Qly. 25 ST Version Type APGE 2.5 (4 Version Order No. 151840000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 Ory. 50 ST Version Type APG 2.5 L. B. Version Order No. 1513830000 Plug. 2.5 mm²,	Oty. Type Order No. GTIN (EAN) Oty. Type Order No. GTIN (EAN) Oty. Type Order No. Oty.	50 ST APGSR 2.5/4 2457580000 4050118472998 25 ST APGSR 2.5/4 - 4P 2457590000 4050118472967 25 ST	Strain relief (terminal), Wemid, orange Version
Type APGS 2.5/4 Version GTIN (EAN) 2487,880,000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050 118472988 Usesion GTIN (EAN) 4950 118472987 Version Order No. 2487,880,000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4950 118472987 Version Order No. 2457,800,000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4950 118472929 Version Order No. 25,574 Version Order No. 25,875 2000 Locking clips (terminal), Wemid, orange GTIN (EAN) 4050 118473100 Locking clips (terminal), Wemid, orange GTIN (EAN) 4050 118473100 Locking clips (terminal), Wemid, orange GTIN (EAN) 4050 118473100 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 1514500000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050 118322002 Depth: 14.27 mm, V-0 Type APG 2.5 L Version Order No. 1513830000 Plug. 2.5 mm², 800 V, 24 A, Number	Type Order No. GTIN (EAN) Oty. Type Order No. GTIN (EAN) Oty. Type Order No.	APGSR 2.5/4 2457580000 4050118472998 25 ST APGSR 2.5/4 - 4P 2457590000 4050118472967 25 ST	Strain relief (terminal), Wemid, orange Version
Order No. 2457580000 Strain relief (terminal), Wemid, orange GTIN (EAN) APGSR 2.5/4.4P Version Order No. 2457590000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050118472967 Version Order No. 2457690000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050118472929 Version Order No. 2457590000 Strain relief (terminal), Wemid, orange GTIN (EAN) 40501184739100 Version Order No. 2457570000 Locking clips (terminal), Wemid, orange GTIN (EAN) 4050118473100 Version Oty 25 ST Version Order No. 1513650000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, Order No. 15136820000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, Order No. 1513880000 Plug. 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 405011832163 Version Order No. 1513880000 Plug. 2.5 mm², 800 V, 24 A. Number of poles: 1, blue GTIN (EAN) 405011832166	Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type Order No.	2457580000 4050118472998 25 ST APGSR 2.5/4 - 4P 2457590000 4050118472967 25 ST	Strain relief (terminal), Wemid, orange Version
GTIN (EAN) 4050118472998 Ory 25 ST Type APGSR 2.5(4 - 4P) Version Order No. 2457590000 Strain relief (terminal), Wernid, orange GTIN (EAN) 4050118472987 Order No. 2457600000 Strain relief (terminal), Wernid, orange GTIN (EAN) 4050118472929 Order No. 2457600000 Strain relief (terminal), Wernid, orange GTIN (EAN) 4050118472929 Ory 25 ST Type APGE 2.5(4 Version Order No. 24576700000 Locking clips (terminal), Wernid, orange GTIN (EAN) 4050118473100 Othy 25 ST Type APGPC 2.5 Version Order No. 1514500000 Terminal Order, orange, Wernid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 Othy 50 ST Type APG 2.5 L Version Order No. 1513830000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321388 Oty 50 ST Type APG 2.5 L Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Oty 50 ST Type APG 2.5 L SI Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Oty 50 ST Type APG 2.5 L SI Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Oty 50 ST Type APG 2.5 MI Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321616 Otyc No ST Type APG 2.5 MI Version Order No. 1513800000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Otyc No ST Type APG 2.5 MI BL Version Order No. 1513800000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Otyc No ST Type APG 2.5 MI BL Version Order No. 1513800000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321630 Otyc No ST Type APG 2.5 MI GN Order No. 1513800000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321630 Otyc No ST Type APG 2.5 MI GN Order No. 1513800000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321456	GTIN (EAN) Oty. Type Order No. GTIN (EAN) Oty. Type Order No.	4050118472998 25 ST APGSR 2.5/4 - 4P 2457590000 4050118472967 25 ST	Version
GTIN (EAN) 4050118472998 Ory. 25 ST Type APGSR 2.5/4 - 4P Order No. 2457580000 GTIN (EAN) 4050118472967 Order No. 2457600000 GTIN (EAN) 4050118472967 Order No. 2457600000 GTIN (EAN) 4050118472989 Order No. 2457600000 GTIN (EAN) 4050118472989 Order No. 2457600000 GTIN (EAN) 4050118473100 Order No. 2457600000 GTIN (EAN) 4050118473100 Order No. 2457600000 GTIN (EAN) 4050118473100 Order No. 2457600000 Order No. 3154500000 Order No. 3154500000 Order No. 4050118473100 Order No. 50 ST Type APG 2.5 L Version Order No. 405018322002 Order No. 405018321000 Order No. 50 ST Type APG 2.5 L Version Order No. 50 ST Type APG 2.5 L Version Order No. 1513830000 Order No. 1513850000 Order No. 15138500000 Order No. 1513850000 Order No. 15138500000 O	Oty. Type Order No. GTIN (EAN) Oty. Type Order No.	4050118472998 25 ST APGSR 2.5/4 - 4P 2457590000 4050118472967 25 ST	Version
Qty. 25 ST Version Order No. 2457589000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050118472967 Ozy. Qty. 25 ST Version Order No. 2457690000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050118472929 Oty. 25 ST Type APGLE 2.5/4 Version Order No. 2457570000 Locking clips (terminal), Wemid, orange GTIN (EAN) 4050118473100 Quy. Qty. 25 ST Version Order No. 1514500000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 Qty. 50 ST Version Order No. 1513830000 Plug. 2.5 mm³, 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 Plug. 2.5 mm³, 800 V, 24 A, Number of poles: 1, blue Type APG 2.5 L BL Version Order No. 1513840000 Plug. 2.5 mm³, 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN)	Oty. Type Order No. GTIN (EAN) Oty. Type Order No.	25 ST APGSR 2.5/4 - 4P 2457590000 4050118472967 25 ST	
Type APGSR 2.5/4 - 4P Version Strain relief (terminal), Wemid, orange (STIN (EAN) 4060118472967 Onc. 2457580000 Strain relief (terminal), Wemid, orange (STIN (EAN) 4060118472967 Onc. 2457600000 Strain relief (terminal), Wemid, orange (STIN (EAN) 4060118472929 Onc. 2457600000 Strain relief (terminal), Wemid, orange (STIN (EAN) 4060118472929 Onc. 2457570000 Cocking clips (terminal), Wemid, orange (STIN (EAN) 4060118473100 Onc. 2457570000 Cocking clips (terminal), Wemid, orange (STIN (EAN) 4060118473100 Onc. 2457570000 Cocking clips (terminal), Wemid, orange (STIN (EAN) 4060118322002 Onc. 2457600000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, Onc. 2457600000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, Onc. 2457600000 Onc. 2457600000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, Onc. 2457600000 Onc. 24576000000 Onc. 245760000000 Onc. 245760000000 Onc. 24576000000000000000000000000000000000000	Type Order No. GTIN (EAN) Oty. Type Order No.	APGSR 2.5/4 - 4P 2457590000 4050118472967 25 ST	
Order No. 2457590000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050118472967 Version Order No. 2467600000 Strain relief (terminal), Wemid, orange GTIN (EAN) 405011847929 Version QIV. 25 ST Version Order No. 2457500000 Locking clips (terminal), Wemid, orange GTIN (EAN) 4050118473100 Otty. QIV. 25 ST Version Order No. 1514500000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 QIV. 50 ST Type Order No. 1513830000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 Otter No. GTIN (EAN) 4050118321388 Otter No. DYPe APG 2.5 L BL Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321818 Otty QIV. 50 ST Version T	Order No. GTIN (EAN) Oty. Type Order No.	2457590000 4050118472967 25 ST	
GTIN (EAN) 4050118472967 Order No. 24576000000	GTIN (EAN) Qty. Type Order No.	4050118472967 25 ST	
Qty. 25 ST Version Order No. 2457600000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050118472929 Oty. Qty. 25 ST Type Type APGLE 2.5/4 Version Order No. 2457570000 Locking clips (terminal), Wemid, orange GTIN (EAN) 4050118473100 Oty. Qty. 25 ST Version Order No. 1514500000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 Qty. 50 ST Version Type APG 2.5 L Version Qty. 50 ST Version Type APG 2.5 L BL Version Qty. 50 ST Version Type APG 2.5 L BL Version Qty. 50 ST Version Type APG 2.5 L GN Version Qty. 50 ST Version Type APG 2.5 L GN Version Qty.	Oty. Type Order No.	25 ST	
Type APGSR 2.5/4 - 8P Version Order No. 2457600000 Otty 25 ST Type APGLE 2.5/4 Version Otty 25 ST Type APGRE 2.5/4 Version Otty 25 ST Type APGRE 2.5 Mere APGRE 3.5 Mere	Type Order No.		
Order No. 2457600000 Strain relief (terminal), Wemid, orange GTIN (EAN) 4050118472929 Uersion Order No. 2457570000 Locking clips (terminal), Wemid, orange GTIN (EAN) 4050118473100 Locking clips (terminal), Wemid, orange GTIN (EAN) 405011832100 Locking clips (terminal), Wemid, orange GTIN (EAN) 405011832100 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 GTIN (EAN) 50 ST Version Type APG 2.5 L Version Order No. 15.13830000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 OV, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 OV, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 OV, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 OV, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Plug, 2.5 mm², 800 V, 24 A, Number of	Order No.	AI GOIT 2.5/ + GI	Version
GTIN (EAN) 4050118472929 Ozy. 25 ST		2457600000	
Qty. 25 ST Type APGLE 2.6/4 Version Order No. 2457570000 Locking clips (terminal), Wernid, orange GTIN (EAN) 4050118473100 Oty. Qty. 25 ST Version Type APGPC 2.5 Version Order No. 1514500000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 Qty. 50 ST Version Order No. 1513830000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 Version Order No. 1513840000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Version Order No. 1513850000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Version Order No. 1513880000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 <td></td> <td></td> <td>Guan Teller (terminal), Wernia, Guinge</td>			Guan Teller (terminal), Wernia, Guinge
Type APGLE 2.5/4 Version Corder No. 2457570000 Locking clips (terminal), Wemid, orange GTIN (EAN) 4050118321300 Cly. 25 ST Type APGPC 2.5 Version Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 Cly. 50 ST Type APG 2.5 L Version Depth: 14.27 mm, V-0 Cly. 50 ST Type APG 2.5 L Version Order No. 1513830000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 Cly. 50 ST Type APG 2.5 L BL Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Cly. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Cly. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Cly. 50 ST Type APG 2.5 MI Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Cly. 50 ST Type APG 2.5 MI Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Cly. 50 ST Type APG 2.5 MI BL Version Order No. 151380000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Cly. 50 ST Type APG 2.5 MI GN Version Order No. 151380000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Cly. 50 ST Type APG 2.5 MI GN Version Order No. 1513830000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Cly. 50 ST			
Order No. 2457570000 Locking clips (terminal), Wernid, orange GTIN (EAN) 4050118473100 Oty. 25 ST Type APGPC 2.5 Version Order No. 1514500000 Terminal cover, orange, Wernid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 Oty. 50 ST Version Order No. 1513830000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321633 Version Order No. 1513840000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Version Order No. 1513850000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Version Order No. 1513880000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Version Order No.<			V
GTIN (EAN) 4050118473100 City. 25 ST Type APGPC 2.5 Version Order No. 1514500000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 City. 50 ST Type APG 2.5 L Version Order No. 1513830000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321633 City. 50 ST Type APG 2.5 L BL Version Order No. 1513840000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 City. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 City. 50 ST Type APG 2.5 MI Version Order No. 1513850000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321630 City. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 City. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321432 City. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 City. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321436			
Oty. 25 ST Type APGPC 2.5 Version Order No. 1514500000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 Oty. 50 ST Version Type APG 2.5 L Version Order No. 1513830000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050118321623 Usersion Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, blue GTIN (EAN) 4050118321388 Usersion Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, green GTIN (EAN) 4050118321616 Usersion Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, blue GTIN (EAN) 4050118321432 Usersion Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A. Number of poles: 1, blue			Locking clips (terminal), Wemid, orange
Type APGPC 2.5 Version Order No. 1514500000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 Order No. 1513830000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 Oty. 50 ST Type APG 2.5 L BL Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Oty. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321616 Oty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Oty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST			
Order No. 1514500000 Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm, GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-0 Qty. 50 ST Version Type APG 2.5 L Version Order No. 1513830000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Cty. Sty 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Order No. Order No. 1513890000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Cty. Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 8	Qty.		
GTIN (EAN) 4050118322002 Depth: 14.27 mm, V-O City. 50 ST Type APG 2.5 L Version Order No. 1513830000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 City. 50 ST Type APG 2.5 L BL Version Order No. 1513840000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 City. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 City. 50 ST Type APG 2.5 MI Version Order No. 1513850000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 City. 50 ST Type APG 2.5 MI Version Order No. 1513850000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 City. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 City. 50 ST Type APG 2.5 MI GN Version Order No. 1513900000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 City. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321432 City. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	Туре	APGPC 2.5	Version
Oty. 50 ST Type APG 2.5 L Version Order No. 1513830000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 Oversion Order No. 1513840000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Oversion Order No. 1513850000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Oversion Order No. 1513880000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Oversion Order No. 1513890000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321432 Oversion Order No. 1513900000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oversion Order No. 1513930000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321436 Oversion Order No. 1513930000 Plug. 2.5 mm², 800 V, 24 A, Number of poles: 1, green </td <td>Order No.</td> <td><u>1514500000</u></td> <td>Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm,</td>	Order No.	<u>1514500000</u>	Terminal cover, orange, Wemid, Height: 10.1 mm, Width: 4.8 mm,
Type APG 2.5 L Version Order No. 1513830000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 Cty. 50 ST Type APG 2.5 L BL Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Cty. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Cty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Cty. 50 ST Type APG 2.5 MI BL Version Order No. 1513800000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Cty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Cty. 50 ST Type APG 2.5 MI GN Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Cty. 50 ST Type APG 2.5 MI GN Version Order No. 15139300000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321432 Cty. 50 ST	GTIN (EAN)	4050118322002	Depth: 14.27 mm, V-0
Order No. 1513830000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321623 Version Type APG 2.5 L BL Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321436 Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456 Version	Qty.	50 ST	
GTIN (EAN) 4050118321623 Qty. 50 ST Type APG 2.5 L BL Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Qty. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Qty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Qty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321432 Qty. 50 ST Type APG 2.5 MI GN Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Qty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321432 Qty. 50 ST	Туре	APG 2.5 L	Version
Oty. 50 ST Type APG 2.5 L BL Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Version Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Oty. Oty. 50 ST Version Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. Oty. 50 ST Version Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456 Version	Order No.	<u>1513830000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige
Type APG 2.5 L BL Version Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Oty. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Oty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	GTIN (EAN)	4050118321623	
Order No. 1513840000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321388 Qty. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Qty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Qty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Qty. 50 ST Type APG 2.5 MI GN Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Qty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	Qty.	50 ST	
GTIN (EAN) 4050118321388 Oty. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Oty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	Туре	APG 2.5 L BL	Version
Oty. 50 ST Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Version Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green	Order No.	<u>1513840000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue
Type APG 2.5 L GN Version Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321616 Oty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	GTIN (EAN)	4050118321388	
Order No. 1513850000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green Oty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	Qty.	50 ST	
GTIN (EAN) 4050118321616 Qty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Qty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Qty. 50 ST Type APG 2.5 MI GN Version Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	Туре	APG 2.5 L GN	Version
Qty. 50 ST Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Qty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Qty. Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	Order No.	<u>1513850000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green
Type APG 2.5 MI Version Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	GTIN (EAN)	4050118321616	
Order No. 1513880000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige GTIN (EAN) 4050118321630 Qty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Qty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	Qty.	50 ST	
GTIN (EAN) 4050118321630 Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456	Туре	APG 2.5 MI	Version
GTIN (EAN) 4050118321630 Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456		<u>1513880000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige
Oty. 50 ST Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Qty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456			
Type APG 2.5 MI BL Version Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456			
Order No. 1513900000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, blue GTIN (EAN) 4050118321432 Qty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456			Version
GTIN (EAN) 4050118321432 Oty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456			
Qty. 50 ST Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456			G, ,
Type APG 2.5 MI GN Version Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green GTIN (EAN) 4050118321456			
Order No. 1513930000 Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green 4050118321456			Version
GTIN (EAN) 4050118321456			
			1 rag, 2.0 mm , 300 v, 27 A, Rullibol of polos. 1, globil
(Lity. 50 5)	` '		
			v ·
Type APG 2.5 R Version			
Order No. <u>1513940000</u> Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, dark beige			Plug, 2.5 mm ² , 800 V, 24 A, Number of poles: 1, dark beige
GTIN (EAN) 4050118321548	Qty.	50 ST	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

T	ADC OF D.D.	Version
Type	APG 2.5 R BL	Version
Order No.	<u>1513950000</u>	Plug, 2.5 mm ² , 800 V, 24 A, Number of poles: 1, blue
GTIN (EAN)	4050118321647	
Qty.	50 ST	
Туре	APG 2.5 R GN	Version
Order No.	<u>1513980000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 1, green
GTIN (EAN)	4050118321470	
Qty.	50 ST	
Туре	APG 2.5/1	Version
Order No.	<u>1513720000</u>	Plug, 2.5 mm ² , 800 V, 24 A, Number of poles: 1, dark beige
GTIN (EAN)	4050118321326	
Qty.	50 ST	
Туре	APG 2.5/10	Version
Order No.	<u>1513770000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 10, dark beige
GTIN (EAN)	4050118321487	
Qty.	20 ST	
Туре	APG 2.5/2	Version
Order No.	<u>1513640000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 2, dark beige
GTIN (EAN)	4050118321180	
Qty.	25 ST	
Туре	APG 2.5/3	Version
Order No.	<u>1513650000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 3, dark beige
GTIN (EAN)	4050118321340	· · · · · · · · · · · · · · · · · · ·
Qty.	25 ST	
Туре	APG 2.5/3-BG-BL-GN	Version
Order No.	1513820000	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 3, dark beige
GTIN (EAN)	4050118321449	riug, 2.5 mm , 000 V, 24 A, Number of poles. 5, dark beige
Qty.	25 ST	
Туре	APG 2.5/4	Version
Order No.	1513670000	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 4, dark beige
GTIN (EAN)	4050118321524	Flug, 2.5 min-, 600 V, 24 A, Number of poles. 4, dark beige
Qty.	25 ST	
		v ·
Туре	APG 2.5/4-3BG-GN	Version
Order No.	<u>1513790000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 4, dark beige
GTIN (EAN)	4050118321364	
Qty.	25 ST	
Туре	APG 2.5/5	Version
Order No.	<u>1513680000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 5, dark beige
GTIN (EAN)	4050118321333	
Qty.	25 ST	
Туре	APG 2.5/5-3BG-BL-GN	Version
Order No.	<u>1513780000</u>	Plug, 2.5 mm ² , 800 V, 24 A, Number of poles: 5, dark beige
GTIN (EAN)	4050118321357	
Qty.	25 ST	
Туре	APG 2.5/6	Version
Order No.	<u>1513690000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 6, dark beige
GTIN (EAN)	4050118321463	
Qty.	25 ST	
Туре	APG 2.5/7	Version
Order No.	<u>1513700000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 7, dark beige
GTIN (EAN)	4050118321296	
Qty.	25 ST	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Type	APG 2.5/8	Version
Order No.	<u>1513730000</u>	Plug, 2.5 mm², 800 V, 24 A, Number of poles: 8, dark beige
GTIN (EAN)	4050118321425	
Qty.	20 ST	
Туре	APG 2.5/9	Version
Type Order No.	APG 2.5/9 1513740000	Version Plug, 2.5 mm², 800 V, 24 A, Number of poles: 9, dark beige
	,	

DEK 5/5



WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Туре	DEK 5/5 MM WS	Version
Order No.	2007110000	Dekafix, Terminal marker, 5 x 5 mm, Weidmueller, white
GTIN (EAN)	4050118391862	
Qty.	800 ST	

Creation date 01.12.2025 11:35:43 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

WS 8/5



WS/DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Туре	WS 8/5 MM WS	Version
Order No.	2007150000	WS, Terminal marker, 8 x 5 mm, Weidmueller, white
GTIN (EAN)	4050118392029	
Qty.	800 ST	

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/5 MC NE BL	Version
Order No.	1609801693	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397166	Weidmueller, blue
Qty.	1000 ST	
Туре	DEK 5/5 MC NE BR	Version
Type Order No.	DEK 5/5 MC NE BR 1249870000	Version Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
• •	, '	

Creation date 01.12.2025 11:35:43 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Туре	DEK 5/5 MC NE GE	Version
Order No.	1609801687	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397135	Weidmueller, yellow
Qty.	1000 ST	
Туре	DEK 5/5 MC NE GN	Version
Order No.	1609801688	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397142	Weidmueller, green
Qty.	1000 ST	
Туре	DEK 5/5 MC NE GR	Version
Order No.	1609801691	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397159	Weidmueller, grey
Qty.	1000 ST	
Туре	DEK 5/5 MC NE OR	Version
Order No.	1238340000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118062632	Weidmueller, orange
Qty.	1000 ST	
Туре	DEK 5/5 MC NE RT	Version
Order No.	<u>1609801686</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397128	Weidmueller, red
Qty.	1000 ST	
Туре	DEK 5/5 MC NE SW	Version
Order No.	1457550000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118263817	Weidmueller, black
Qty.	1000 ST	

V0



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/5 MC NE VO WS	Version
Order No.	1388530000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118188622	Weidmueller, white
Qty.	1000 ST	

Creation date 01.12.2025 11:35:43 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/5 MC NE VI	Version
Order No.	1249860000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118042764	Weidmueller, violet
Qty.	1000 ST	
Туре	DEK 5/5 MC NE WS	Version
Type Order No.	DEK 5/5 MC NE WS 1609801044	Version Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
	, '	

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/5 MC SDR	Version
Order No.	<u>1609810000</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190456597	Weidmueller, To customer specification
Qty.	200 ST	

Creation date 01.12.2025 11:35:43 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/5 PLUS MC NE GE	Version
Order No.	<u>1907520000</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4032248532100	Weidmueller, yellow
Qty.	1000 ST	
Туре	DEK 5/5 PLUS MC NE WS	Version
Type Order No.	DEK 5/5 PLUS MC NE WS 1854490000	Version Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
	, '	

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/5 PLUS MC SDR	Version
Order No.	<u>1854500000</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4032248393602	Weidmueller, To customer specification
Qty.	200 ST	

Creation date 01.12.2025 11:35:43 MEZ





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/5 S MC NE WS
Order No.	1341620000
GTIN (EAN)	4050118145793
Qty.	400 ST

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, white

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/5 S MC SDR	Version
Order No.	1341590000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118146042	Weidmueller, To customer specification
Qty.	80 ST	

Creation date 01.12.2025 11:35:43 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

End bracket









Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Туре	AEB 35 SC/1 BK	Version
Order No.	2475310000	A-series, End bracket
GTIN (EAN)	4050118487114	
Qty.	50 ST	
Туре	AEB 35 SC/1	Version
Type Order No.	AEB 35 SC/1 1991920000	Version A-series, End bracket
	,	

Marker holder



The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snaped together and could be mounted in all standard marking channels of the Klippon® Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

General ordering data

Туре	BZT 1 WS 10/5	Version
Order No.	<u>1805490000</u>	Accessories, Marker holder
GTIN (EAN)	4032248270231	
Qty.	100 ST	
Туре	BZT 1 ZA WS 10/5	Version
Type Order No.	BZT 1 ZA WS 10/5 1805520000	Version Accessories, Marker holder
	·	

Creation date 01.12.2025 11:35:43 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

End bracket










Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Туре	AEB 35 SCL/1 V0	Version
Order No.	<u>2661280000</u>	A-series, End bracket
GTIN (EAN)	4050118702163	
Qty.	20 ST	
Туре	AEB 35 SCL/1 VO BK	Version
Order No.	2661300000	A-series, End bracket
GTIN (EAN)	4050118702187	
Qty.	20 ST	
Туре	AEB 35 SCL/1 VO GY	Version
Order No.	2661290000	A-series, End bracket
GTIN (EAN)	4050118702170	
Qty.	20 ST	

Slotted screwdriver



VDE insulated screwdriver sets, for working on live parts up to 1000 V AC and 1500 V DC, DIN EN 60900. IEC 900. Each piece is "GS" safety tested. Blade made from fully hardened, high-alloy chromium-vanadium-molybdenum steel, gun-metal finish.

General ordering data

Туре	SDIS SLIM 0.6X3.5X100	Version
Order No.	2749610000	Mounting tool, Blade width (B): 3.5 mm, Blade length: 100 mm, Blade
GTIN (EAN)	4050118896350	thickness (A): 0.6 mm
Qty.	1 ST	

Creation date 01.12.2025 11:35:43 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

End plates and partition plates



End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal finger-proof.

General ordering data

Туре	SEP PGTB 2T 2.5 6C	Version
Order No.	3096200000	End plate for terminals, dark beige, Height: 112.92 mm, Width: 2.1
GTIN (EAN)	4099987120951	mm, V-0, Wemid, Snap-on: Yes
Qty.	20 ST	

Plugs







The plugs for our WeiCoS-System are available for all different connection systems. The product range includes preassembled connectors from 1 to 10 poles and the possibility of an individual assembly. This ensures maximum flexibility for every application. The customized accessories increase the safety and protection against environmental influences.

General ordering data

oraoring aata	
SPG 2.5 L	Version
<u>3030160000</u>	Plug (terminal), SNAP IN, 2.5 mm ² , 24 A, 800 V, Number of
4099986973183	connections: 1, Number of poles: 1, Width: 5.1 mm
50 ST	
SPG 2.5 L BL	Version
3030290000	Plug (terminal), SNAP IN, 2.5 mm ² , 24 A, 800 V, Number of
4099986973312	connections: 1, Number of poles: 1, Width: 5.1 mm
50 ST	
SPG 2.5 L GN	Version
3030240000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
4099986973268	connections: 1, Number of poles: 1, Width: 5.1 mm
50 ST	
SPG 2.5 MI	Version
3030090000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
4099986973114	connections: 1, Number of poles: 1, Width: 5.1 mm
50 ST	
SPG 2.5 MI BL	Version
3030260000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
<u>3030260000</u> 4099986973282	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of connections: 1, Number of poles: 1, Width: 5.1 mm
	3030160000 4099986973183 50 ST SPG 2.5 L BL 3030290000 4099986973312 50 ST SPG 2.5 L GN 3030240000 4099986973268 50 ST SPG 2.5 MI 3030090000 4099986973114 50 ST

Creation date 01.12.2025 11:35:43 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

_	ODO O E MILONI	V :
Туре	SPG 2.5 MI GN	Version
Order No.	3030220000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
GTIN (EAN)	4099986973244	connections: 1, Number of poles: 1, Width: 5.1 mm
Qty.	50 ST	
Туре	SPG 2.5 R	Version
Order No.	3030190000	Plug (terminal), SNAP IN, 2.5 mm ² , 24 A, 800 V, Number of
GTIN (EAN)	4099986973213	connections: 1, Number of poles: 1, Width: 5.1 mm
Qty.	50 ST	
Type	SPG 2.5 R BL	Version
Order No.	3030300000	Plug (terminal), SNAP IN, 2.5 mm ² , 24 A, 800 V, Number of
GTIN (EAN)	4099986973329	connections: 1, Number of poles: 1, Width: 5.1 mm
Qty.	50 ST	
Туре	SPG 2.5 R GN	Version
Order No.	3030210000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
GTIN (EAN)	4099986973237	connections: 1, Number of poles: 1, Width: 5.1 mm
Qty.	50 ST	
Туре	SPG 2.5/1	Version
Order No.	3030250000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
GTIN (EAN)	4099986973275	connections: 1, Number of poles: 1, Width: 5.1 mm
Qty.	50 ST	
Туре	SPG 2.5/10	Version
Order No.	3030100000	Plug (terminal), SNAP IN, 2.5 mm ² , 24 A, 800 V, Number of
GTIN (EAN)	4099986973121	connections: 10, Number of poles: 10, Width: 51 mm
Qty.	10 ST	
Туре	SPG 2.5/2	Version
Order No.	3030170000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
GTIN (EAN)	4099986973190	connections: 2, Number of poles: 2, Width: 10.2 mm
Qty.	40 ST	
Туре	SPG 2.5/3	Version
Order No.	3030200000	Plug (terminal), SNAP IN, 2.5 mm ² , 24 A, 800 V, Number of
GTIN (EAN)	4099986973220	connections: 3, Number of poles: 3, Width: 15.3 mm
Qty.	25 ST	
Туре	SPG 2.5/3-BG-BL-GN	Version
Order No.	3030270000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
GTIN (EAN)	4099986973299	connections: 3, Number of poles: 3, Width: 15.3 mm
Qty.	30 ST	
Туре	SPG 2.5/4	Version
Order No.	3030150000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
GTIN (EAN)	4099986973176	connections: 4, Number of poles: 4, Width: 20.4 mm
Qty.	20 ST	
Туре	SPG 2.5/4-3BG-GN	Version
Order No.	3030230000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
GTIN (EAN)	4099986973251	connections: 4, Number of poles: 4, Width: 20.4 mm
Qty.	20 ST	
Туре	SPG 2.5/5	Version
Order No.	3030130000	Plug (terminal), SNAP IN, 2.5 mm ² , 24 A, 800 V, Number of
GTIN (EAN)	4099986973152	connections: 5, Number of poles: 5, Width: 25.5 mm
Qty.	20 ST	
Туре	SPG 2.5/5-3BG-BL-GN	Version
Order No.	3030280000	Plug (terminal), SNAP IN, 2.5 mm ² , 24 A, 800 V, Number of
GTIN (EAN)	4099986973305	connections: 5, Number of poles: 5, Width: 25.5 mm
Qty.	20 ST	
	-	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Type	SPG 2.5/6	Version
• •		
Order No.	3030140000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
GTIN (EAN)	4099986973169	connections: 6, Number of poles: 6, Width: 30.6 mm
Qty.	20 ST	
Туре	SPG 2.5/7	Version
Order No.	3030110000	Plug (terminal), SNAP IN, 2.5 mm², 24 A, 800 V, Number of
GTIN (EAN)	4099986973138	connections: 7, Number of poles: 7, Width: 35.7 mm
Qty.	20 ST	
Туре	SPG 2.5/8	Version
Order No.	3030120000	Plug (terminal), SNAP IN, 2.5 mm ² , 24 A, 800 V, Number of
OTINI /F A A II		
GTIN (EAN)	4099986973145	connections: 8, Number of poles: 8, Width: 40.8 mm
Qty.	4099986973145 10 ST	connections: 8, Number of poles: 8, Width: 40.8 mm
, ,		connections: 8, Number of poles: 8, Width: 40.8 mm Version
Qty.	10 ST	
Qty.	10 ST SPG 2.5/9	Version