# **TS35X15 ST POK 1222**



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

#### Similar to illustration



The Klippon® POK enclosure range is made from a highquality glass fibre reinforced polyester and is ideal for applications and environments where corrosion resistance, impact resistance and a high IP protection class are a requirement.

Key features of the extensive product range:

- Available in 17 sizes
- Two standard finishes (colours): grey (similar to RAL 7001 for industrial use) and black (similar to RAL 9011 for harsh environments, Ex)
- Cover with stainless steel screws in cross-head / slotted design
- Moulded gasket made of silicone or chloroprene
- Fixing holes outside the sealed area to ensure high ingress protection of IP66
- Impact resistance up to 7 Joules
- Mounting directly in the enclosure or using an internal mounting plate
- Direct wall mounting possible using fixing holes or mounting feet
- · Fastening thread to attach mounting rails and plates
- Up to E60 fire rating dependent on the configuration
- Weidmüller can manufacture and supply this enclosure to match customer specifications - fitted with all necessary terminals and cable glands.

### **General ordering data**

Version	Rail, TS 35, TS 35 x 15, with slot, Steel, galvanic zinc plated and passivated	
Order No.	8000073209	
Туре	TS35X15 ST POK 1222	
GTIN (EAN)	4064675356561	
Qty.	20 items	



# **TS35X15 ST POK 1222**



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

Approvals					
ROHS	Conform				
Dimensions and weights	<b>:</b>				
Depth	15 mm	Depth (inches)	0.5906 inch		
Height	35 mm	Height (inches)	1.378 inch		
Width	205 mm	Width (inches)	8.0709 inch		
Net weight	145 g				
Temperatures					
Operating temperature					
Environmental Product (	Compliance				
RoHS Compliance Status	Compliant without exemption				
REACH SVHC	No SVHC above 0.1 wt%				
General information	'				
Material thickness	1.5 mm	Installation advice	Direct mounting		
Standards	DIN EN 60715	Surface finish	galvanic zinc plated and passivated		
Basic material	Steel	Integral fixing	Screwed		

### Classifications

ETIM 8.0	EC001285	ETIM 9.0	EC001285
ETIM 10.0	EC001285	ECLASS 14.0	27-40-06-02
ECLASS 15.0	27-40-06-02		

Creation date 03.12.2025 06:22:26 MEZ

Catalogue status / Drawings 2