

FBCON SS DP PCG TERM 24V

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com



For Profibus DP and Modbus RS485, FBCon standard T-distributors and terminators connect individual field devices or remote I/O to the bus cable. Their EMC cable glands, protection class IP66 and a wide operating temperature range safely protect your connections in harsh environments.

Functionality

- EMC cable glands for trunk and spurs
- M12 connector for spurs
- External earthing stud
- Pressure equalizing element
- Protection class IP66
- Aluminium and stainless-steel versions
- Profibus DP / Modbus RS485 compatible

Note: The use of FBCon products with aluminum enclosures and / or M12 connectors is not recommended in strongly saline environments.

General ordering data

Version	Standard distributor with bus termination (active), Terminator, IP65, IP66
Order No.	8714240000
Type	FBCON SS DP PCG TERM 24V
GTIN (EAN)	4032248404704
Qty.	1 items

FBCON SS DP PCG TERM 24V

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS Conform

UL File Number Search [UL Website](#)

Certificate no. (cULus) E141197

Dimensions and weights

Depth	47.5 mm	Depth (inches)	1.8701 inch
Height	47.5 mm	Height (inches)	1.8701 inch
Width	79.5 mm	Width (inches)	3.1299 inch
Net weight	404 g		

Temperatures

Storage temperature	-25 °C...75 °C	Operating temperature	-40 °C...80 °C
Humidity	5...95 %, no condensation		

Probability of failure

SIL in compliance with IEC 61508 None

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c, 7a, 7cl
REACH SVHC	Lead 7439-92-1
SCIP	3a5f5913-76fc-4ff5-8563-4463f80bbe02

Connection data

Clamping range, min.	4 mm ²	Clamping range, max.	6 mm ²
----------------------	-------------------	----------------------	-------------------

Technical data

Number of poles	3	Connection type PE	Spur line with cable gland
Type of distribution	Terminator	Design of housing	With pressure compensation element
Housing main material	Stainless steel, rust-proof	Cable entry	plastic screwed cable gland, Round
Conductor O.D., max.	9.5 mm	Conductor O.D., min.	6.5 mm
Type of mounting	surface-mounted	Protection degree	IP65, IP66
Pollution severity	3	Bus system	Profibus-DP, Modbus RS485
Operating voltage	30 V	Housing surface	polished
Operating voltage U _{max} , max.	30 V DC		

Part description

Product description
 The device is an active terminating resistor for the fieldbus system Profibus PA. The device complies with protection class IP66/IP67. Functional description: The device connects one field device with one fieldbus segment. The device supports earthing concepts with multi-point screen earthing or single-point screen earthing. The earthing concepts are explained in the Profibus guidelines.

FBCON SS DP PCG TERM 24V

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Classifications

ETIM 8.0	EC001604	ETIM 9.0	EC001604
ETIM 10.0	EC001604	ECLASS 14.0	27-44-01-11
ECLASS 15.0	27-44-01-11		

