

IE-C6FS8UG0015A40A40-G

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



Assembled IE cables, patch cable Cabinet Line, Cat. 6,
PUR, green

General ordering data

| | |
|------------|---|
| Version | System cable, RJ45 IP 20, RJ45 IP 20, <20 m: Cat.6A / >20 m Class EA (ISO/IEC 11801 2010), PUR, 1.5 m |
| Order No. | 8941350015 |
| Type | IE-C6FS8UG0015A40A40-G |
| GTIN (EAN) | 4050118089707 |
| Qty. | 1 items |

Technical data

Approvals

Approvals



| | |
|-------------------------|----------------------------|
| ROHS | Conform |
| UL File Number Search | UL Website |
| Certificate no. (cULus) | E316369 |

Dimensions and weights

| | | | |
|------------|-------|-----------------|--------------|
| Length | 1.5 m | Length (inches) | 59.0551 inch |
| Net weight | 54 g | | |

Temperatures

| | | | |
|--------------------------|----------------|-----------------------|----------------|
| Storage temperature | -40 °C...85 °C | Operating temperature | -40 °C...85 °C |
| Installation temperature | -10 °C...60 °C | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Cable specific standards

| | | | |
|--|--|------------------------|--------------------------|
| Generic communication cable facilities | ISO / IEC 11801:2002, ANSI / TIA / EIA-568-B.2-10, EN 50173-1:2007 | Corrosiveness of fumes | According to EN50288-2-2 |
|--|--|------------------------|--------------------------|

Electrical properties

| | |
|------------|----------------------------|
| PoE / PoE+ | conforming to IEEE 802.3at |
|------------|----------------------------|

General standards

| | | | |
|--------------------|----------------|-------------------------|---------|
| Connector standard | IEC 60603-7-51 | Certificate no. (cULus) | E316369 |
|--------------------|----------------|-------------------------|---------|

Standards

| | | | |
|------------------------|--------------------------|--|--|
| Connector standard | IEC 60603-7-51 | Generic communication cable facilities | ISO / IEC 11801:2002, ANSI / TIA / EIA-568-B.2-10, EN 50173-1:2007 |
| Corrosiveness of fumes | According to EN50288-2-2 | | |

Cable structure

| | | | |
|-----------------------|--|---------------------------|--------------|
| Strands | 7 | Sheathing colour | green |
| Cross-section | 4*2*AWG 27/7 - 4*2*0.1 mm ² | Shielding | S/FTP |
| Number of wires | 8 | Insulation cross-section | 1.02 mm |
| Insulation | PE | Sheath diameter, max. | 6.4 mm |
| Sheath diameter, min. | 6 mm | Material sheath | PUR |
| Wire pair shielding | Aluminium foil | Arrangement of wire cores | Twisted pair |

IE-C6FS8UG0015A40A40-G

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

| | | | |
|--------------------|---|---------------------------------------|--|
| Complete shielding | Shielding braid made from copper wiring | Overlap of shielding braid | 60 % |
| Wire material | Stranded tin-plated copper wire | Colour sequence or wires - wire pairs | white - blue, white - orange, white - green, white - brown |

Electrical properties of cable

| | | | |
|--------------------------------|---|-------------------------|---|
| Transmission rate | 10 Gbit/s | Category | <20 m: Cat.6A / >20 m Class EA (ISO/IEC 11801 2010) |
| Capacity at 1 kHz | 46 nF/km | Signal propagation time | 4.27 ns/m |
| Test voltage: wire-wire-shield | 750 V DC, 1 min | Delay skew | 25 ns/100m |
| Characteristic impedance | 100 ± 15 Ω at 1–100 MHz, 100 ± 22 Ω at 100–250 MHz, 100 ± 25 Ω at 250–600 MHz | | |

Mechanical and material properties of cable

| | | | |
|---------------------------------|----------------------------------|--------------------------------|--|
| Resistance to oils | in accordance with IEC 60811-2-1 | Silicone-free | Yes |
| UV-resistant | Yes | Halogen | halogen-free, according to IEC 60754-2 |
| Min. bending radius, repetitive | 10 x cable diameter | Min. bending radius, once only | 5 x cable diameter |
| Abrasion resistance | very good | Resistance to spread of flame | in accordance with IEC 60332-1 / UL 1581 FT2 |
| Corrosiveness of fumes | According to EN50288-2-2 | | |

Plug

| | | | |
|------------|---|-----------|---|
| Plug right | RJ45, IP20, male contact, straight, plug, Plastic, shielded | Plug left | RJ45, IP20, male contact, straight, plug, Plastic, shielded |
|------------|---|-----------|---|

Plug, left

| | |
|-----------|---|
| Plug left | RJ45, IP20, male contact, straight, plug, Plastic, shielded |
|-----------|---|

Plug, right

| | |
|------------|---|
| Plug right | RJ45, IP20, male contact, straight, plug, Plastic, shielded |
|------------|---|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC002599 | ETIM 9.0 | EC002599 |
| ETIM 10.0 | EC002599 | ECLASS 14.0 | 27-06-03-08 |
| ECLASS 15.0 | 27-06-03-08 | | |

Drawings

Wiring

Dimensioned drawing

| | | | | |
|------|---|----------------|---|------|
| RJ45 | 1 | white (orange) | 1 | RJ45 |
| | 2 | orange | 2 | |
| | 3 | white (green) | 3 | |
| | 4 | blue | 4 | |
| | 5 | white (blue) | 5 | |
| | 6 | green | 6 | |
| | 7 | white (brown) | 7 | |
| | 8 | brown | 8 | |

Accessories

Blank



TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are various different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Pre-attachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the PrintJet CONNECT, plotter or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-Ink or STI pen in connection with CLI T sleeves

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| | | |
|------------|----------------------------|---|
| Type | TM-I 12 MC NE WS | Version |
| Order No. | 1718411044 | TM-I, Insert markers, 12 x 4 mm, white |
| GTIN (EAN) | 4008190348977 | |
| Qty. | 320 ST | |
| Type | TM-I 18 MC NE WS | Version |
| Order No. | 1718431044 | TM-I, Insert markers, 1.5 - 22 mm, 18 x 4 mm, white |
| GTIN (EAN) | 4008190349011 | |
| Qty. | 320 ST | |