CUTTER 20 A

Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools (KT 8 to KT 22) also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/ IEC 60900.

General ordering data

Version	Cutting tool for one-hand operation
Order No.	9040140000
Type	CUTTER 20 A
GTIN (EAN)	4008190467098
Qty.	1 items

Creation date 13.03.2026 06:29:21 MEZ

CUTTER 20 A

Technical data

Dimensions and weights

Depth	31 mm	Depth (inches)	1.2205 inch
Height	71.5 mm	Height (inches)	2.815 inch
Width	245 mm	Width (inches)	9.6456 inch
Net weight	443.7 g		

Environmental Product Compliance

RoHS Compliance Status	Not affected
REACH SVHC	Lead 7439-92-1
SCIP	cf06c250-ed1e-4a45-9c1b-c5c8cbf13bf0

Technical data

Description of article	Front cable cutter up to 20 mm cable diameters	Version	One-hand mechanical

Cutting tools

Copper cable - solid, max. (AWG)	3 AWG	Copper cable - solid, max.	25 mm²
Copper cable - flexible, max. (AWG)	3/0 AWG	Copper cable - flexible, max.	95 mm²
Copper cable - stranded, max. (AWG)	1 AWG	Copper cable - stranded, max.	50 mm²
Copper cable, max. diameter	22 mm	Data / telephone / control cable, max. Ø	22 mm
Single-core aluminium cable, max.(mm²)	50 mm²	Stranded aluminium cable, max. (AWG)	2/0 AWG
Stranded aluminium cable, max (mm²)	70 mm²	Stranded aluminium cable, max. diameter	22 mm

Classifications

ETIM 8.0	EC000142	ETIM 9.0	EC000142
ETIM 10.0	EC000142	ECLASS 14.0	21-04-47-01
ECLASS 15.0	21-04-47-01		