

**POS-4P M12 PG13,5 150MM**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com



Various build-in connectors are required for the connections on the device side of the sensor/actuator cabling. These are available in the versions M12, M8 and M5.

**General ordering data**

Version	Locating plug-in connector, M12, pin, straight, Number of poles: 4
Order No.	<a href="#">9455650000</a>
Type	POS-4P M12 PG13,5 150MM
GTIN (EAN)	4008 190076467
Qty.	1 items

**POS-4P M12 PG13,5 150MM**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data**
**Approvals**

ROHS	Conform
------	---------

**Dimensions and weights**

Net weight	66 g
------------	------

**Environmental Product Compliance**

RoHS Compliance Status	Compliant
REACH SVHC	Lead 7439-92-1
SCIP	ebf89fc8-a87f-4691-b87a-dfb9921774b4

**Technical specifications for cable**

Cable length	0.15 m	Sheathing colour	silver
Core cross-section	1.5 mm <sup>2</sup>	Shielded	No
Halogen	No	Insulation	not available
Sheath material	Nickel-plated CuZn	Colour coding	brown, blue, black
Number of poles	4		

**Technical data customisable plug-in connectors**

Number of poles	4	Coding	A-coded
Contact surface	Gold-plated	LED	No
Housing main material	CuZn, nickel-plated	Nominal voltage	250 V
Nominal current	4 A	Protection degree	IP67
Cable gland	PG 13.5	Temperature range of housing	-40 ... +85 ° C

**General data**

Number of poles	4	Cable length	0.15 m
Coding	A-coded	Connection thread	M12
Contact surface	Gold-plated	Sheathing colour	silver
Core cross-section	1.5 mm <sup>2</sup>	Housing main material	CuZn, nickel-plated
Nominal voltage	250 V	Nominal current	4 A
Protection degree	IP67	Cable gland	PG 13.5
Basic material	Cu Zn	Fire behaviour	V2
Connection 1	M12	Connection 2	Flying wires
Sheath material	Nickel-plated CuZn	Temperature range of housing	-40 ... +85 ° C
Conductor O.D.	-		

**Classifications**



ETIM 8.0	EC002599	ETIM 9.0	EC002599
ETIM 10.0	EC002599	ECLASS 14.0	27-06-03-08
ECLASS 15.0	27-06-03-08		

## POS-4P M12 PG13,5 150MM

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

## Drawings

[www.weidmueller.com](http://www.weidmueller.com)



## Pole scheme