

## **QL 3 SAKK10**



Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

## **General ordering data**

| Version    | Cross-connector (terminal), when screwed in, grey, 57 A, Number of poles: 3, Pitch in mm (P): 11.50, Insulated: No, Width: 31.1 mm |
|------------|------------------------------------------------------------------------------------------------------------------------------------|
| Order No.  | <u>9502660000</u>                                                                                                                  |
| Туре       | QL 3 SAKK10                                                                                                                        |
| GTIN (EAN) | 4008190550622                                                                                                                      |
| Qty.       | 50 items                                                                                                                           |



## **QL 3 SAKK10**



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

## **Technical data**

| Approvals                 |                             |                     |                 |
|---------------------------|-----------------------------|---------------------|-----------------|
| ROHS                      | Conform                     |                     |                 |
|                           | Comorni                     |                     |                 |
| Dimensions and weights    | 1                           |                     |                 |
| Depth                     | 1 mm                        | Depth (inches)      | 0.0394 inch     |
| Height                    | 6 mm                        | Height (inches)     | 0.2362 inch     |
| Width                     | 31.1 mm                     | Width (inches)      | 1.2244 inch     |
| Net weight                | 1.36 g                      |                     |                 |
| Temperatures              |                             |                     |                 |
| Storage temperature       | -25 °C55 °C                 | Ambient temperature | -5 °C40 °C      |
| Environmental Product C   | ompliance                   |                     | '               |
| D 110 0 1' 0' '           | 0 15 4 34 4                 |                     |                 |
| RoHS Compliance Status    | Compliant without exemption |                     |                 |
| REACH SVHC                | No SVHC above 0.1 wt        | 70                  |                 |
| Material data             |                             |                     |                 |
| Basic material            | Copper                      | Colour              | grey            |
| System specifications     |                             |                     |                 |
| Version                   | Cross-connector             |                     |                 |
| Additional technical data |                             |                     | 1               |
|                           |                             |                     |                 |
| Type of fixing            | when screwed in             | Installation advice | Direct mounting |
| Explosion-tested version  | No                          | Type of mounting    | when screwed in |
| Dimensions                |                             |                     |                 |
| Pitch in mm (P)           | 11.50 mm                    |                     |                 |
| General                   |                             |                     |                 |
| Number of poles           | 3                           | Installation advice | Direct mounting |
| Rating data               |                             |                     |                 |
| Name in all assumption    | F.7. A                      |                     |                 |
| Nominal current           | 57 A                        |                     | <u> </u>        |
| Classifications           |                             |                     |                 |
| ETIM 6.0                  | EC000489                    | ETIM 7.0            | EC000489        |
| ETIM 8.0                  | EC000489                    | ETIM 9.0            | EC000489        |
| ETIM 10.0                 | EC000489                    | ECLASS 9.0          | 27-14-11-40     |
| ECLASS 9.1                | 27-14-11-40                 | ECLASS 10.0         | 27-14-11-40     |
| ECLASS 11.0               | 27-14-11-40                 | ECLASS 12.0         | 27-14-11-40     |
| ECLASS 13.0               | 27-25-03-03                 | ECLASS 14.0         | 27-25-03-03     |
| ECLASS 15.0               | 27-25-03-03                 |                     | ·               |

Creation date 27.11.2025 03:04:14 MEZ

Catalogue status / Drawings 2