

## AC SB M 250A 4POL CG 06KV

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

### Datos generales para pedido

Versión	Fotovoltaico, Interruptor, Interruptor separador, 600 V AC, 250 A, 4 polos, Interruptor manual
Código	<a href="#">3103200000</a>
Tipo	AC SB M 250A 4POL CG 06KV
GTIN (EAN)	4099987148405
Cantidad	1 Pieza

## AC SB M 250A 4POL CG 06KV

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Datos técnicos

### Homologaciones

Homologaciones



ROHS Conformidad

### Dimensiones y pesos

Profundidad	215 mm	Profundidad (pulgadas)	8.4645 inch
Altura	360 mm	Altura (pulgadas)	14.1732 inch
Anchura	270 mm	Anchura (pulgadas)	10.6299 inch
Peso neto	4130 g		

### Temperaturas

Temperatura ambiente -25 °C...55 °C

### Datos generales

Tipo de protección IP65

### Seccionador bajo carga

Tipo de tensión	AC	Tensión nominal	400 V
Corriente nominal	250 A	Número de contactos como contacto normalmente cerrado	0
Corriente nominal de ruptura de carga principalmente activa	250 A	Corriente nominal de cierre en cortocircuito	20 kA
Corriente nominal de pico soportada	12 kA	Clase de resistencia mecánica	M2 (5000)
Número de contactos como contacto normalmente abierto	4		

### Clasificaciones

ETIM 7.0	EC000216	ETIM 8.0	EC000216
ETIM 9.0	EC004830	ETIM 10.0	EC004830
ECLASS 11.0	27-07-02-03	ECLASS 12.0	27-07-02-03
ECLASS 13.0	27-07-02-03	ECLASS 14.0	27-07-02-03
ECLASS 15.0	27-07-02-03		

### Bases de licitación

Especificación larga  
 Load break Switch in polyester housing.  
 Suitable for disconnection on the AC side.  
 Number of poles: 4  
 Rated operational current (Ie) (Ie):  
 - according to IEC (AC-21): 250 A  
 Rated operational voltage (Ue):  
 - according to IEC: 690 V  
 Suitability for use:  
 Emergency Stop Switch:  
 No

### AC SB M 250A 4POL CG 06KV

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

## Datos técnicos

[www.weidmueller.com](http://www.weidmueller.com)

Main Switch: Yes Number of contacts normally open: 4  
Number of contacts normally closed: 0  
Number of switching positions: 2  
Lockable: Yes  
The switch is mounted using 4 screws.  
Protection class (IP): 65  
Dimensions HxWxD: 360x270x215 mm.  
Approved according to Low-voltage Switchgear and Controlgear: IEC 60947-3, DIN VDE 0660 Part 107 (EN 60947-3)

