

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com



一般注文データ

バージョン	太陽光発電, スイッチ, 断路器, AC600 V, 125 A, 4 極, 手動式スイッチ
注文番号	<u>3103180000</u>
種別	AC SB M 125A 4POL CG 06KV
GTIN (EAN)	4099987148382
数量	1 items

カタログステータス / 図面 1



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

MAMID承認件数



適合 ROHS

寸法と重量

深さ	142 mm	奥行き (インチ)	5.5905 inch
高さ	320 mm	 高さ(インチ)	12.5984 inch
幅	205 mm	 幅(インチ)	8.0709 inch
正味重量	1773 g		

温度

周囲温度 -25 °C...55 °C

一般データ

保護度合い IP65

負荷ブレークスイッチ

電圧種別	AC	公称電圧	415 V
公称電流	125 A	NC接点としての接点数	0
定格メインアクティブ負荷遮断電流	125 A	接続の種別	耐張クランプ接続
定格短絡投入電流	2.1 kA	定格ピーク耐電流	2.5 kA
機械的耐久性クラス	M2 (10000)	NO接点としての接点数	4

分類

ETIM 7.0	EC000216	ETIM 8.0	EC000216
ETIM 9.0	EC004830	ETIM 10.0	EC004830
ECLASS 11.0	27-07-02-03	ECLASS 12.0	27-07-02-03
ECLASS 13.0	27-07-02-03	ECLASS 14.0	27-07-02-03
ECLASS 15.0	27-07-02-03		

入札仕様書

長体仕様 Load break Switch in polyester housing.

Suitable for disconnection on the AC side. Number of poles: 4 Rated operational current (le) (le):

- according to IEC (AC-21): 125 A

Rated operational voltage

(Ue):

- according to IEC: 415 V Suitability for use: **Emergency Stop Switch:**

Main Switch: Yes Number of contacts normally open:

4

2 カタログステータス / 図面



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

技術データ

Number of contacts normally closed: 0
Number of switching positions: 2
Lockable: Yes
The switch is mounted using 4 screws.
Protection class (IP): 65
Polyester housing with knockouts for cable glands.
Dimensions HxWxD: 320x205x142 mm.
Approved according to Low-voltage Switchgear and Controlgear: IEC 60947-3, DIN VDE 0660 Part 107 (EN 60947-3)



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

図面







